

SAT LITE[®]

By General Mfg., Inc.

ZIP-SHIP[™] CATALOG

ZIP SHIP[™]
ALL MODELS SHIP
WITHIN 48 HOURS!

STUBBY[®] LED

Features

- LED LAMP ASSEMBLY PRODUCES 520 LUMENS OF BRIGHT 4000K COLORED LIGHT.
- RUGGEDIZED LED DRIVER IN THE LAMP IS DESIGNED TO LAST.
- LIGHT SMOOTHING TECHNOLOGY[™] VIRTUALLY ELIMINATES GLARE AND SHADOWS.
- COVERED ON-OFF SWITCH UNDER DOMED END CAP IS PROTECTED FROM DIRT AND MOISTURE.
- TWIN STEEL HOOK IS UNBREAKABLE.
- THICK WALL POLYCARBONATE OUTER TUBE IS VIRTUALLY UNBREAKABLE!
- THE LED LAMP IS AVAILABLE AS A CONVENIENT REPLACEMENT PART.

NEW!!

**Model No.
1940-4011**



**Model No.
1925-4009**

Models

Model No.	Description	Case Qty
1925-4009	Stubby LED on 25' 18/2 SJTOW-A	6
1940-4011	Stubby LED on 40' 18/2 SJTOW-A	4
5165-0223	Stubby LED Headkit for 18ga SJT Cord	-

SAFTLITE®

By General Mfg., Inc.

Features

- SIDE WORK LIGHT PRODUCES 562 LUMENS OF BRIGHT 5000K WHITE LIGHT, RATED AT 50,000 HOURS.
- 3-WATT FLASHLIGHT PROVIDES A BRIGHT 125 LUMEN SPOTLIGHT OUT THE END.
- COVERED ON-OFF SWITCH IN HANDLE IS PROTECTED FROM DIRT AND MOISTURE.
- LIGHT SMOOTHING TECHNOLOGY™ VIRTUALLY ELIMINATES SHADOWS AND GLARE!
- INLINE TOOL TAP KEEPS 120V POWER OUTLET SAFELY AWAY FROM USER'S HANDS

Cord Models

Model No.	Description	Case Qty
1901-2008	Stubby II LED 1' 16/3 SJTOW-A Cord	6
1925-2023	Stubby II LED 25' 18/2 SJTOW-A	6
1925-2025	Stubby II LED 25' SJTOW-A w/ 12A TT	6
5165-0202	Stubby II LED Headkit 18/2, 18/3, 16/2	-
5165-0203	Stubby II LED Headkit for 16/3 SJT	-

Reel Models

Model No.	Description	Case Qty
1935-8006	Stubby II LED 35' Reel w/ 12 amp TT	4
1940-8011	Stubby II LED 40' 18/2 SJTOW-a Cord	4

STUBBY® II LED

Model No.
1940-8011



Features

- FOUR 1-WATT LEDs WITH 120-DEGREE ANGLE PROVIDE EQUIVALENT LIGHT PATTERN TO A FLUORESCENT LAMP AND GENERATE 600 LUMENS.
- ONE 1-WATT HIGH OUTPUT LENSED END LED PROVIDES A BRIGHT FLASHLIGHT.
- COVERED ON/OFF SWITCH CONTROLS SIDE AND END LEDs.
- POLYCARBONATE OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- 7.4 VOLT LI-ION RECHARGEABLE BATTERY PACK OPERATES THE LIGHT FOR 5-6 HOURS STRAIGHT WHEN FULLY CHARGED.
- “UNIVERSAL” CHARGER (100VAC-240VAC, 50/60HZ) WILL DROP TO A TRICKLE CHARGE WHEN BATTERY IS FULLY CHARGED.
- LITHIUM ION BATTERY RESISTS MEMORY FORMATION.
- CHARGER MEETS CEC (CALIFORNIA COMPLIANT)
- DISPOSE OF LITHIUM-ION BATTERY PACKS IN COMPLIANCE WITH LOCAL LAWS.

Models

Model No.	Description
2302-0011	Stubby II Cordless, charger, 1 battery
5000-1618	Battery Charger
5000-1639	Battery Pack, rechargeable, 7.4 L-Ion

STUBBY® II LED CORDLESS

Model No.
5000-1639

Model No.
2302-0011



Model No.
5000-1618

Features

- 210 SERIES LED LIGHTS HAVE A DOUBLE ROW OF LEDs THAT PRODUCE 2400 LUMENS TOTAL.
- 5000K BRIGHT WHITE LIGHT AND ARE RATED TO 50,000-HOUR LIFE.
- INLINE ON-OFF SWITCH IS COVERED AND PROTECTED FROM DIRT AND MOISTURE.
- THICK POLYCARBONATE OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- ANTI-ROLL SOFT END CAPS ABSORB IMPACTS WHEN THE LIGHT IS DROPPED
- DRIVER SEALED INSIDE THE LIGHT FIXTURE WILL OPERATE ON 120VAC - 240VAC , 50/60HZ.
- OIL RESISTANT, WEATHER TIGHT, COLD WEATHER RATED SJEOW CORD WITH GROUNDED PLUG.

LED MAINTENANCE LIGHTS



**Model No.
2020-4000**

Models

Model No.	Description	Fixture Length	Lumens	Case Qty
2020-4000	210 Series LED, 20 Watt, 25' Cord	27"	2400	4

LED MACHINE LIGHTS



**Model No.
2010-3000**

- 110 SERIES LED LIGHTS HAVE A SINGLE ROW OF LEDs AND RANGE FROM 1200 TO 2400 LUMENS.
- 5000K BRIGHT WHITE LIGHT AND ARE RATED TO 50,000-HOUR LIFE.
- THICK POLYCARBONATE OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- DRIVER SEALED INSIDE THE LIGHT FIXTURE WILL OPERATE ON 120VAC - 240VAC , 50/60HZ.
- OIL RESISTANT, WEATHER TIGHT, SJTOW CORD WITH GROUNDED PLUG.

Models

Model No.	Description	Fixture Length	Lumens	Case Qty
2010-3000	110 Series LED, 10 Watt, 25' Cord	27"	1200	4
2020-3003	110 Series LED, 20 Watt, 25' Cord	51"	2400	4

SAFTLITE®

By General Mfg., Inc.

Features

- 10.5" COMPACT LENGTH.
- 13-WATT FLUORESCENT ROUGH SERVICE BULB IS 10X MORE IMPACT RESISTANT THAN STANDARD BULBS.
- LIGHT OUTPUT IS 825 LUMENS OF BRIGHT 5000K COLORED LIGHT.
- LAMP IS RATED FOR 10,000 HOURS.
- ON/OFF SWITCH IS PROTECTED UNDER SOFT DOMED END CAP
- TWIN STEEL HOOK
- TOUGH-SHIELD™ POLYCARBONATE OUTER TUBE IS VIRTUALLY UNBREAKABLE.

Cord Model

Model No.	Description	Case Qty
1413-2500	Stubby 25' 18/2 SJTOW-A Cord	12
1413-5000	Stubby 50' 18/2 SJTOW-A Cord	12
5165-9501	Stubby Headkit for 18ga SJT Cord	-

Reel Model

Model No.	Description	Case Qty
3313-4000	Stubby 40' Reel 18/2 SJTOW-A Cord	4

STUBBY®

**Model No.
3313-4000**



STUBBY® II



**Model No.
1113-2500**

Features

- 13-WATT ROUGH SERVICE PLS 13 FLUORESCENT LAMP PRODUCES 825 LUMENS OF BRIGHT 5000K COLORED LIGHT.
- LAMP IS RATED FOR 10,000 HOURS.
- VIRTUALLY UNBREAKABLE POLYCARBONATE TOUGH-SHIELD™ OUTER TUBE.
- SJTOW-A, OIL RESISTANT, WEATHER TIGHT CORDS.
- ON-OFF SWITCH IN HANDLE IS PROTECTED BY SOFT HANDLE GRIP.
- SOFT BUMPERS AND LAMP CUSHION HELP PROTECT THE LAMP.
- TWIN STEEL HOOK

Cord Models

Model No.	Description	Case Qty
1113-0101	Stubby II, 1' 16/3 SJTOW-A Cord	12
1113-2500	Stubby II, 25' 18/2 SJTOW-A Cord	12
5165-9519	Stubby II Headkit, 16/3 SJTOW-A	-
5165-9520	Stubby II Headkit 18/2, 18/3, 16/2	-
5165-9529	Stubby II Headkit 18ga SJT no Ballast	-

Reel Models

Model No.	Description	Case Qty
3613-4000	Stubby II 40' Reel 18/2 SJTOW-A Cord	4
3613-4001	Stubby II 40' Reel SJTOW w/ 12A TT	4



Features

- 22" LIGHT STRETCHES LIGHT OVER A LARGER AREA.
- LIGHT OUTPUT IS 870 LUMENS OF BRIGHT 4100K COLORED LIGHT.
- F15T8CW LAMP IS RATED FOR UP TO 7500 HOURS.
- LAMP IS ULTRA-COOL OPERATING.
- POLYCARBONATE OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- PROTECTED ON-OFF SWITCH UNDER SOFT DOMED END CAP.
- 18/2 SJTOW-A OIL RESISTANT, WEATHER TIGHT CORD.
- TWIN STEEL HOOK

COMPACT 15 WATT FLUORESCENT



**Model No.
1215-2500**

Models

Model No.	Description	Case Qty
1215-2500	15W, 22" Length, 25' Cord	12

TWIN TUBE FLUORESCENT MAINTENANCE LIGHT



**Model No.
1650-3015**

Features

- 50 WATT LAMP PRODUCES 3750 LUMENS OF LIGHT AND IS RATED AT 14,000 HOURS.
- TOUGH-SHIELD™ OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- 16/3 SJEOW CORD IS OIL RESISTANT, WEATHER TIGHT AND COLD WEATHER RATED, & REMAINS FLEXIBLE.
- 120VAC ELECTRONIC BALLAST IS PROTECTED INSIDE THE LIGHT FIXTURE.
- 24 AND 36-WATT MODELS COME WITH A VERTICAL HANGING HOOK, 50-WATT MODELS COME WITH HORIZONTAL HOOK.
- THICK ANTI-ROLL END CAPS PROVIDE IMPACT PROTECTION.
- PROTECTED INLINE ON-OFF SWITCH.
- ALL PARTS ARE MOUNTED TO A FULL-LENGTH ALUMINUM EXTRUDED BACKBONE FOR EXTRA DURABILITY AND EASE OF SERVICE.

Models

Model No.	Description	Case Qty
1650-3015	50W, Ballast in Head, 25' Cord	4

HANGING OPTIONS LARGE DIAMETER LIGHTS

Mounting Options - Large Diameter Lights

Model No.	Description	Quantity
5000-0862	48" Adjustable Hanging Kit	2
5000-1051	Direct Mount Bracket	1
5000-1062	Machine Bracket Mount	1
5000-1077	Magnetic Mount	1



Model No.
5000-0862



Model No.
5000-1051



Model No.
5000-1062



Model No.
5000-1077

HANGING OPTIONS SMALL DIAMETER LIGHTS

Mounting Options - Small Diameter Lights

Model No.	Description
1060-4034	L Grip, 3/4 x 6 flex Neck, 80# Magnet
5000-1030	Magmount, M Grip, 80# Magnet



Model No.
5000-1030



Model No.
1060-4034

SAF-T-POWER[®]

By General Mfg., Inc.

Features

- 9" DIAMETER STEEL REEL HANDLES 30' OF 16/3 SJT CORD WITH SAF-T-LOK[™] OUTLET
- LOCKING OUTLET, NEVER ACCIDENTALLY UNPLUG AGAIN!
- 16-GAUGE MODELS STANDARD.
- TRIPLE OUTLET WITH 10AMP CIRCUIT BREAKER.
- BALL STOP AND ADJUSTER TO SET THE HANG-DOWN HEIGHT OF THE OUTLETS.
- WALL AND CEILING MOUNT HARDWARE PACKAGE IS INCLUDED.

COMMERCIAL REEL



**Model No.
2640-5001**

Models

Model No.	Description	Case Qty
2630-3000	Triple Outlet, 10Amp, 30' 16/3, SJT	4
2640-5001	Saf-T-Lok [™] , 10 Amp, 40' 16/3, SJTOW	4

MIDSIZE REEL



**Model No.
2200-3000**

Features

- 40' 12/3 SJTW RETRACTING CORD WITH TRIPLE OUTLET.
- 15AMP WITH INTEGRATED CIRCUIT BREAKER AT THE TRI TAP.
- 27" POWER INLET CORD COMES WITH MOLDED NEMA 5-15P GROUNDING PLUG.
- STEEL MOUNTING BRACKET WITH STEEL LOCKING PIN AND SAFETY CHAIN CAN BE USED TO MOUNT THE REEL TO THE CEILING OR THE WALL.
- SPECIALLY BLENDED PLASTIC IS EXTREMELY DURABLE.

Model

Model No.	Description	Case Qty
2200-3000	Midsize Reel, 40' Cord, Triple Outlet	2

SAF-T-POWER™

INDUSTRIAL POWER SUPPLY



**Model No.
4040-3203**

FEATURES: 4040-3203

- ADJUSTABLE GUIDE ARM FOR CEILING, WALL OR BENCH MOUNT.
- GUIDE ARM HAS ROLLERS TO ALLOW SMOOTH, EVEN PAYOUT AND TAKE-UP OF CORD.
- BALL STOP ALLOWS USER TO SET HANG-DOWN HEIGHT OF THE RETRACTING CORD.
- 40' 12/3 SJTOW RETRACTING CORD
- LIGHTED SAF-T-LOK™ OUTLET RATED FOR 15 AMPS.
- SAF-T-LOK™, NEVER ACCIDENTLY UNPLUG AGAIN!
- 5.5' POWER INLET CORD WITH NEMA 5-15P GROUNDED PLUG.

FEATURES: 4550-5101

- ADJUSTABLE GUIDE ARM FOR CEILING, WALL OR BENCH MOUNT.
- GUIDE ARM HAS ROLLERS TO ALLOW SMOOTH PAYOUT AND TAKE-UP OF CORD.
- BALL STOP ALLOWS USER TO SET HANG-DOWN HEIGHT OF THE RETRACTING CORD.
- 50' 12/3 SJTOW RETRACTING CORD
- 20 AMP DUPLEX OUTLET WITH GFCI PROTECTION
- 5.5' POWER INLET CORD WITH NEMA 5-20P GROUNDED PLUG.



**Model No.
4550-5101**

Models

Model No.	Description	Case Qty
4040-3203	Series 4000 Reel, 40 ft, 15A, Saf-T-Lok™	1
4550-5101	Series 5500 Reel, 50 ft, 20A Duplex	1

General Manufacturing, Inc.
1336 W Wiley Avenue
Bluffton, IN 46714
Phone: 260.824.3440
sales@saftlite.com
www.saftlite.com

By General Mfg., Inc.