SATE PULL

By General Mfg., Inc.



ALL MODELS WITH 48 HOURS!



POWR TM By General Mfg., Inc.

SAF-T-LITE® Power Supply Reels help you get power where you need it! Models are available ranging from 30' to 50' retracting cord length. Models are also available with single or triple outlet and with or without circuit breaker. Saf-T-Lite commercial power supply reels come with 18 or 16-gauge cord. The model with white cord is perfect for a clean look in office and retail floor use.



COMMERCIAL POWER SUPPLY REELS

Model No. 2630-3000



Features

- -9" DIAMETER STEEL REEL HANDLES 30' OF 16/3 SJT. CORD FOR HEAVIER AMPERAGE USE OR 50' OF 18/3 SVT CORD FOR LONGER REACH.
- 30' 16-GAUGE CORD REEL IS AVAILABLE IN ALL WHITE FOR CLEAN LOOK FOR RETAIL SPACES.
- 16-GAUGE MODELS WITH TRIPLE OUTLET COME WITH CIRCUIT BREAKER IN THE OUTLETS.
- 18-GAUGE MODEL COMES WITH SINGLE OUTLET AND CIR-CUIT BREAKER AT THE PLUG.
- ALL MODELS COME WITH BALL STOP AND ADJUSTER TO SET THE HANG-DOWN HEIGHT OF THE OUTLETS.
- WALL AND CEILING MOUNT HARDWARE PACKAGE IS IN-CLUDED WITH ALL REELS.





SHE CON HEER

Model No.	Description	Outlet	Amp	GFCI/	Retracting	Pigtail Cord	Cord Specs	Case	Case
Std. Tube		Type	Rating	Breaker	Cord Specs	Specs		Qty.	Weight
2630-1000	Power Reel	Single	10 amps	None	30' 16/3	2' 16/3	SJT	4	34 lbs.
2630-3000	Power Reel	Triple	10 amps	Breaker	30' 16/2	2' 16/3	SJT	4	36 lbs.
2630-3019	Power Reel, white cord	Triple	10 amps	Breaker	30' 16/3	2' 16/3	SJT	4	36 lbs.
2650-1000	Power Reel	Single	7 amps	Breaker	50' 18/2	2' 18/2	SVT	4	33 lbs.



Tired of having to take down the reel from a ceiling to service a work light? Ever wished you had more than one light for those special jobs? The Saf-T-Lok power supply reel can be mounted on the wall or ceiling and can be used as a standard power supply reel or use with any of our short-corded lights and make the Saf-T-Lok reel a light reel. Simply plug in the light and never accidently unplug again! To release the plug, simply slide the release collar back and pull the plug from the outlet. So, whether you are using a light, saw or any other corded tool, rest assured you will not accidently unplug the tool!





el No. 1113-0101

SAR-T-LOK POWER REELS







Features

- -9" DIAMETER STEEL REEL HOUSING.
- 16/3 SJT TYPE CORD RATED FOR UP TO 10 AMPS.
- Use as a standard power supply reel or plug in a light and use as a light reel.
- Locking feature prevents accidental unplugging at the worst possible time!
- 2' 16/3 SJT POWER INLET CORD WITH MOLDED NEMA 5-15P GROUNDED PLUG.
- A VARIETY OF SHORT CORDED WORK LIGHTS ARE AVAILABLE TO MAKE THE SAF-T-LOK OUTLET A MULTI TASK POWER SUPPLY REEL!



SHEOON JEEU

	Model No. Std. Tube	Description	Outlet Type	Amp Rating		Retracting Cord Specs	Pigtail Cord Specs	Cord Specs	Case Qty.	Case Weight
	2630-1016	Saf-T-Lok Reel	Single	10 amps	No	30' 16/3	2' 16/3	SJT	4	34 lbs.
2	2640-5001	Saf-T-Lok Reel	Single	10 amps	No	40' 16/3	2' 16/3	SJTOW	4	38 lbs.





SAF-T-LITE MID SIZE POWER SUPPLY REEL DELIVERS POWER WHERE YOU NEED IT. WITH THE REMOVAL OF A LOCKING PIN, THE REEL CAN BE CARRIED TO A DIFFERENT WORK SIDE AND THEN RETURNED WHEN THE JOB IS COMPLETE. THE MID SIZE POWER SUPPLY REEL IS AVAILABLE WITH TRIPLE OUTLET AS WELL AS THE SAF-T-LOK OUTLET.





Features

- -40' 12/3 SJTW RETRACTING CORD WITH TRIPLE OUTLET OR SAF-T-LOK OUTLET.
- TRIPLE OUTLET MODEL HAS CIRCUIT BREAKER AT THE TRI TAP.
- SAF-T-LOK OUTLET IS LIGHTED, INDICATING POWER IS AVAILABLE!
- -27" Power inlet cord comes with molded NEMA 5-15P grounded plug.
- -STEEL MOUNTING BRACKET WITH SAFETY CHAIN CAN BE USED TO MOUNT THE REEL TO THE CEILING OR THE WALL.
- -SPECIAL BLENDED PLASTIC IS EXTREMELY DURABLE.

POWER SUPPLY REEL





SHELOW TEEN

201	Model No. Std. Tube	Description	Outlet Type	Amp Rating		Retracting Cord Specs	Pigtail Cord Specs	Cord Specs	Case Qty.	Case Weight
7	2200-3000	Mid Size RI.	Triple	15 amps	Yes	40' 12/3	2' 12/3	SJTW-A	2	32 lbs.
2	2200-3011	Mid Size RI.	Saf-T-Lok	15 amps	No	40' 12/3	2' 12/3	SJTW-A	2	32 lbs.



Ever get out to the very end of the cord on the power supply reel and come up just short of the length you need? The Saf-T-Lite Mega Mid-Size Reel is the reel for you. The retracting cord is a full 65' long and has four outlets at the end. Talk about delivering the power where you need it! Take a good look at the Mega Mid-Size Reel, you will be glad you did!



CHECON PEER

Model No.	Description	Outlet	Amp	Circuit	Retracting	Pigtail Cord	Cord Specs	Case	Case
Std. Tube		Туре	Rating	Breaker	Cord Specs	Specs		Qty.	Weight
2201-4000	Mega Mid Size RI.	Quad	15 amps	Yes	65' 12/3	2' 12/3	SJTW-A	2	44 lbs.

The Saf-T-Lite® Series 4000 reel is designed to take the hard, everyday use that industry demands. With industrial grade collector ring, replaceable carbon brushes, and brass transfer rings, our reels are built to last! Models are available with single and duplex outlets.



GFCI Duplex Available



Single Outlet Options

Features

- ADJUSTABLE GUIDE ARM FOR CEILING, WALL OR BENCH MOUNT.
- GUIDE ARM HAS ROLLERS TO ALLOW SMOOTH PAYOUT AND TAKE-UP OF CORD.
- BALL STOP ALLOWS USER TO SET HANG-DOWN HEIGHT OF THE RETRACTING CORD.
- 5.5' Power INLET CORD WITH NEMA 5-15P GROUNDED PLUG.
- The single outlet is rated to 15-amps and 20-amp models are available.
- Never accidently unplug again... If you are using the Saf-T-Lok outlet!
- SAF-T-LOK OUTLET IS LIGHTED, INDICATING POWER IS AVAILABLE.
- Duplex outlets come standard with GFCI Protection.

SERIES 4000 REELS



Model No.	Description	Outlet	Amp	GFCI/	Retracting	Pigtail Cord	Cord Specs	Case	Case
Std. Tube		Туре	Rating	Breaker	Cord Specs	Specs		Qty.	Weight
4040-3203	4000 Reel	Saf-T-Lok	15 amps	None	40' 12/3	5.5' 12/3	SJTOW	1	30 lbs.
4045-3400	4000 Reel	Single	15 amps	None	45' 14/3	5.5' 14/3	SJTOW	1	30 lbs.
4050-3600	4000 Reel	Single	13 amps	None	50' 16/3	5.5' 16/3	SJTOW	1	26 lbs.
4040-4201	4000 Reel	Duplex	20 amps	GFCI	40' 12/3	5.5' 12/3	SJTOW	1	32 lbs.
4045-4401	4000 Reel	Duplex	15 amps	GFCI	45' 14/3	5.5' 12/3	SJTOW-A	1	31 lbs.
4050-4601	4000 Reel	Duplex	13 amps	GFCI	50' 16/3	5.5' 16/3	SJTOW	1	28 lbs.



If you need a reel that handles 50° of cord and be rated for up to 20 amps, the 5505 Series power supply reel is made just for you! Designed to take the hard, everyday use that industry demands, the 5505 reel comes with industrial grade collector ring, replaceable carbon brushes, and brass transfer rings. The spring motor in the 5505 reel is capable of handling 70° of cord, 55° of 12/3 cord on the reel and a minimum 15° hang down.



GFCI Duplex Available

SBRIBS 5505 RBBIA





Features

- REEL COMES WITH ADJUSTABLE GUIDE ARM WITH FOR CEILING, WALL OR BENCH MOUNT.
- GUIDE ARM HAS ROLLER TO ENSURE SMOOTH PAYOUT AND TAKE-UP OF CORD.
- BALL STOP ALLOWS USER TO SET HANG DOWN HEIGHT OF THE RETRACTING CORD.
- -5.5' Power inlet cord with NEMA 5-15P grounded plug.
- -The single outlet is rated to 15-amps and 20-amp models available.
- Never accidently unplug again, if you are using the Saf-T-Lok outlet!
- SAF-T-LOK OUTLET IS LIGHTED, INDICATING POWER IS AVAILABLE.
- Duplex outlets come standard with GFCI Protection.
- 70' REEL MODELS HAVE 55' ON THE REEL AND MUST HAVE AT LEAST A 15' HANG DOWN.





Model No. Std. Tube	Description	Outlet Type	Amp Rating	GFCI/ Breaker	Retracting Cord Specs	Pigtail Cord Specs	Cord Specs	Case Qty.	Case Weight
4550-5101	5505 Reel	Duplex	20 amps	GFCI	50' 12/3	5.5' 12/3	SJTOW	1	40 lbs.
4550-5106	5505 Reel	Saf-T-Lok	15 amps	None	50' 12/3	5.5' 12/3	SJTOW	1	39 lbs.
4570-4000	5505 Reel	Saf-T-Lok	15 amps	None	70' 12/3	5.5' 12/3	SJTOW	1	46 lbs.
4570-8000	5505 Reel	Triple	15 amps	None	70' 12/3	5.5' 12/3	SJTOW	1	46 lbs.

SAIP/PUVR_{TM}



REMARKS DEPONSER SUPPLY REPORT

Model No. 2610-0039

- o 6° Steel reel-side mount bracket
- 10° 16/3 retracting cord with hospital grade plug
- 16/3 Pigiail with hospital grade receptade

REMARKS OF DAMES OF THE SUPPLY RESEARCH

Model No. 2630-1013

- 9^p Steel reel-side mount bracket
- · 30° 16/3 retracting cord with hospital grade plug
- · 2' 16/3 Pigail with hospital grade receptade

General Manufacturing, Inc. 1336 W Wiley Avenue Bluffton, IN 46714 Phone: 260.824.3440 sales@saftlite.com www.saftlite.com

By General Mfg., Inc.

