

# SAT LITE<sup>®</sup>

By General Mfg., Inc.



**ZIP SHIP<sup>™</sup>**  
ALL MODELS WITH **48** Logo  
SHIP WITHIN **48 HOURS!**

LED LIGHTING

# SAFTLITE®

By General Mfg., Inc.

So, WHAT EXACTLY IS LITE SMOOTHING TECHNOLOGY™? THE SHORT ANSWER IS THAT IT IS A PURPOSEFUL DESIGN IN THE SAF-T-LITE STUBBY II LED TO VIRTUALLY ELIMINATE SHADOWS AND SIGNIFICANTLY REDUCE GLARE. ANOTHER FEATURE FOUND IN THE STUBBY II LED IS OUR RUGGEDIZED LED DRIVER. AN LED WORK LIGHT IS ONLY AS GOOD AS ITS WEAKEST COMPONENT. FROM THE COMPONENT SELECTION, TO THE DESIGN OF THE DRIVER BOARD, THE STUBBY II LED IS DESIGNED AND BUILT TO LAST IN THE COMMERCIAL WORK SHOP.



## STUBBY II LED



Model No. 1940-8011

### Features

- SIDE WORK LIGHT PRODUCES 562 LUMENS OF BRIGHT.
- 5000K WHITE LIGHT, RATED AT 50,000 HOURS.
- 3-WATT FLASHLIGHT PROVIDES A BRIGHT 125 LUMEN SPOTLIGHT OUT THE END.
- COVERED ON-OFF SWITCH IN HANDLE IS PROTECTED FROM DIRT AND MOISTURE.
- LIGHT SMOOTHING TECHNOLOGY™ VIRTUALLY ELIMINATES SHADOWS AND GLARE!
- INLINE TOOL TAP KEEPS 120V POWER OUTLET SAFELY AWAY FROM USER'S HANDS.
- MODELS ARE AVAILABLE WITH POLYCARBONATE OUTER TUBE OR X-TREME SHIELD™ CHEMICAL RESISTANT OUTER TUBE.

### CORD MODELS

Model No. Std. Tube	Model No. X-Treme Shield	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Cord Specs	Case Qty.	Case Weight
4/8 1901-2008	Not Available	Stubby II LED	No	N/A	Yes	1'	16/3 SJTOW-A	6	12 lbs.
4/8 1925-2023	1925-2024	Stubby II LED	No	N/A	Yes	25'	18/2 SJTOW-A	6	17 lbs.
4/8 1925-2025	1925-2026	Stubby II LED	Yes	12 amps	Yes	25'	16/3 SJTOW-A	6	24 lbs.
1950-2009	1950-2010	Stubby II LED	Yes	12 amps	Yes	50'	16/3 SJTOW-A	6	35 lbs.
1950-2011	1950-2012	Stubby II LED	No	N/A	Yes	50'	18/2 SJTOW-A	6	24 lbs.

### REEL MODELS

Model No. Std. Tube	Model No. X-Treme Shield	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Pigtail Length	Cord Specs	Case Qty.	Case Weight
4/8 1935-8006	1935-8007	Stubby II LED	Yes	10 amps	Yes	35'	2'	16/3 SJTOW-A	4	39 lbs.
4/8 1940-8011	1940-8012	Stubby II LED	No	N/A	Yes	40'	2'	18/2 SJTOW-A	4	38 lbs.
1940-8021	1940-8022	Stubby II LED	Yes	10 amps	Yes	40'*	2'	16/3 SJTOW-A	4	45 lbs.

\* 35' INSIDE REEL MINIMUM HANG DOWN.



**BUILT WITH PRIDE  
IN THE U.S.A.**

THE EDGE LED IS A COMPACT LED THAT GIVES YOU MORE BANG FOR YOUR BUCK! THE LIGHT IS DURABLE, BRIGHT, AND BUILT IN THE USA! MODELS ARE AVAILABLE ON CORD OR REEL. THE MODEL COMES WITH OUR GEN 1 LIGHT SMOOTHING TECHNOLOGY. GLARE AND SHADOWS ARE SIGNIFICANTLY REDUCED.



**THE EDGE LED**

**Features**

- 4-WATT LED LAMP PRODUCES 350 LUMENS OF 4000K BRIGHT WHITE LIGHT.
- LAMP IS PUT THROUGH AN ADDITIONAL PROCESS AT OUR FACTORY TO MAKE IT ROUGH SERVICE.
- LED LAMP IS EASILY REPLACEABLE AND AVAILABLE AS A REPLACEMENT PART.
- COVERED ON-OFF SWITCH IN HANDLE IS PROTECTED FROM DIRT AND MOISTURE.
- TWIN STEEL HOOK IS UNBREAKABLE.
- LIGHT SMOOTHING TECHNOLOGY REDUCES GLARE AND SHADOWS.
- THICK WALL POLYCARBONATE OUTER TUBE IS BREAK RESISTANT!



**Model No. 1940-3001**

**CORD MODELS**

Model No. Std. Tube	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Cord Specs	Case Qty.	Case Weight
1925-3000	The Edge LED	Yes	12 amps	Yes	25'	16/3 SJTOW-A	6	18 lbs
1925-3002	The Edge LED	No	N/A	Yes	25'	18/2 SJTOW-A	6	12 lbs

**REEL MODELS**

Model No. Std. Tube	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Retracting Cord Specs	Pigtail Length	Cord Specs	Case Qty.	Case Weight
1935-3000	The Edge LED	Yes	10A	Yes	35' 16/3	2'	16/3 SJTOW-A	4	41 lbs.
1940-3000	The Edge LED Auto Reel	No.	N/A	Yes*	40' 18/2	2'	16/3 SJTOW-A	4	36 lbs.
1940-3001	The Edge LED	No	N/A	Yes	40' 18/2	2'	16/3 SJTOW-A	4	41 lbs.

**SWITCH IS LOCATED ON THE REEL. PULL LIGHT DOWN TO TURN ON, RETRACT TO TURN LIGHT OFF.**

LED  
LIGHTING

**SAFTLITE**<sup>®</sup>  
By General Mfg., Inc.

THE STUBBY<sup>®</sup> FLUORESCENT LIGHT WAS INTRODUCED IN 1986 AND SINCE THE BEGINNING HAS CONSISTENTLY BEEN A VERY POPULAR LIGHT. THE STUBBY<sup>®</sup> LED HAS UNSURPASSED DURABILITY, COMPACT SIZE, AND IS ALSO BUILT IN THE USA. AVAILABLE ON CORD OR REEL, THE STUBBY IS ALSO AVAILABLE WITH OPTIONAL TOOL TAP. TRY IT OUT, YOU WILL BE GLAD YOU DID!



**Model No. 1925-4009**

### Features

- LED LAMP ASSEMBLY PRODUCES 520 LUMENS OF BRIGHT 4000K COLORED LIGHT.
- RUGGEDIZED LED DRIVER IN THE LAMP IS DESIGNED TO LAST.
- IN CASE OF FAILURE, THE LED LAMP IS AVAILABLE AS A REPLACEMENT PART.
- COVERED ON-OFF SWITCH UNDER DOMED END CAP IS PROTECTED FROM DIRT AND MOISTURE.
- TWIN STEEL HOOK IS UNBREAKABLE.
- LIGHT SMOOTHING TECHNOLOGY REDUCES GLARE AND SHADOWS.
- THICK WALL POLYCARBONATE OUTER TUBE IS BREAK RESISTANT!



**Model No. 1940-4010**

### CORD MODELS

Model No. Std. Tube	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Cord Specs	Case Qty.	Case Weight
1901-4001	Stubby LED	No	N/A	Yes	1'	16/3 SJTOW-A	6	10 lbs.
1925-4009	Stubby LED	No	N/A	Yes	25'	18/2 SJTOW-A	6	15 lbs.
1925-4010	Stubby LED	Yes	12 amps	Yes	25'	16/3 SJTOW-A	6	22 lbs.

### REEL MODELS

Model No. Std. Tube	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Retracting Cord Specs	Pigtail Length	Cord Specs	Case Qty.	Case Weight
1940-4010	Stubby LED	Yes	10 amps	Yes	40' 16/3	2'	16/3 SJTOW-A	4	41 lbs.
1940-4011	Stubby LED	No	N/A	Yes	40' 18/2	2'	16/3 SJTOW-A	4	36 lbs.
1940-4012	Stubby LED	No	N/A	Yes*	40' 18/2	2'	16/3 SJTOW-A	4	41 lbs.

\*SWITCH IS LOCATED ON THE REEL. PULL LIGHT DOWN TO TURN ON, RETRACT TO TURN LIGHT OFF.

www.saftlite.com



**BUILT WITH PRIDE  
IN THE U.S.A.**

THE MID SIZE REEL BY GENERAL MANUFACTURING IS AVAILABLE WITH THE STUBBY® LED OR STUBBY II® LED. YOU CAN HARDLY GO WRONG! THE REEL IS DESIGNED AS A PORTABLE REEL, OR IT CAN BE PERMANENTLY MOUNTED ON THE CEILING OR WALL. THE STEEL MOUNTING BRACKET WITH LOCKING PIN AND SAFETY CHAIN ENSURE THE REEL WILL STAY MOUNTED IN PLACE.

**MID SIZE REEL WITH  
LED LIGHTS**



**Stubby II with  
3 Watt Endlight**



**Roller Guides**

**Features**

- 50' 16-GAUGE SJTW RETRACTING CORD.
- 27" 12/3 SJTW POWER INLET CORD (PIGTAIL) HAS MOLDED NEMA 5-15P GROUNDED PLUG.
- ROLLERS AT THE OPENING OF THE REEL ENSURE SMOOTH PAYOUT AND TAKE UP.
- SAFETY OF A STEEL MOUNTING BRACKET, LOCKING PIN, AND SAFETY CHAIN.
- REEL CAN BE EASILY REMOVED FROM THE MOUNTING BRACKET AND TAKEN TO JOB SITE.
- PLASTIC REEL HOUSING IS MADE OF A SUPER TOUGH BLENDED PLASTIC.
- LIGHTS ARE AVAILABLE WITH OR WITHOUT TOOL TAP.



**Model No. 1950-4000**



**Mounting Hardware**

**REEL MODELS**

Model No. Std. Tube	Model No. X-Treme Shield	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Pigtail Length	Cord Specs	Case Qty.	Case Weight
1950-8007	1950-8010	Stubby II LED	Yes	10 amps	Yes	50'	27"	16/3 SJTW	2	16 lbs.
1950-8008	1950-8009	Stubby II LED	No	N/A	Yes	50'	27"	16/3 SJTW	2	17 lbs.
1950-4000	N/A	Stubby LED	No	N/A	Yes	50'	27"	16/3 SJTW	2	15 lbs.
1950-4001	N/A	Stubby LED	Yes	10 amps	Yes	50'	27"	16/3 SJTW	2	16 lbs.

LED  
LIGHTING

# SAFT-LITE®

By General Mfg., Inc.

SAF-T-LITE® SERIES 4000 REELS ARE DESIGNED TO LAST IN COMMERCIAL AND INDUSTRIAL ENVIRONMENTS. THE REEL COMES WITH RUGGED STEEL FRAME WITH POWDER COAT FINISH, INDUSTRIAL GRADE COLLECTOR RING, OIL RESISTANT, WATERTIGHT CORD, AND CHOICE OF THE STUBBY® LED OR STUBBY II® LED.

## SERIES 4000 WITH LED LIGHTS



**Adjustable Guide Arm  
Mount to Ceilings,  
Walls, or Benches.**

**Stubby LED Available**



**Model No. 4050-2003**

### Features

- ADJUSTABLE GUIDE ARM FOR WALL, CEILING OR BENCH MOUNT.
- GUIDE ARM HAS ROLLERS TO ALLOW SMOOTH PAYOUT AND TAKE-UP OF CORD.
- SJTOW CORD IS OIL RESISTANT AND WATERTIGHT.
- 5.5' POWER INLET CORD COMES WITH NEMA 5-15P GROUNDED PLUG.
- BALL STOP ALLOWS USER TO SET HANG DOWN HEIGHT OF THE RETRACTING CORD.
- LIGHTS ARE AVAILABLE WITH OR WITHOUT TOOL TAP.

### REEL MODELS

Model No. Std. Tube	Model No. X-Treme Shield	Description	Outlet Y/N	Switch Y/N	Cord Length	Pigtail Length	Cord Specs	Case Qty.	Case Weight
4050-2003	4050-2006	Stubby II LED	No	N/A	50'	5.5'	16/3 SJTOW-A	1	29 lbs.
4050-2004	4050-2005	Stubby II LED	Yes	10 amps	50'	5.5'	16/3 SJTOW-A	1	30 lbs.
4050-4000	Not Available	Stubby LED	No	N/A	50'	5.5'	16/3 SJTOW-A	1	28 lbs.
4050-4001	Not Available	Stubby LED	Yes	10 amps	50'	5.5'	16/3 SJTOW-A	1	29 lbs.



**BUILT WITH PRIDE  
IN THE U.S.A.**

DON'T WORRY ABOUT COMING TO THE END OF YOUR ROPE. GO CORDLESS! THE STUBBY II CORDLESS LED WITH 7.4 VOLT LITHIUM ION BATTERY PACK GIVES YOU THE FREEDOM TO GO ANYWHERE YOUR WORK TAKES YOU. LASTING 6 HOURS STRAIGHT ON A FULLY CHARGED BATTERY, YOU CAN TAKE A SECOND BATTERY PACK AND WORK ALL DAY, PLUS SOME. THE LEDs USED IN THE STUBBY II CORDLESS PROVIDE BRIGHT LIGHT COMPARABLE TO A FLUORESCENT WORK LIGHT. WITH THE END LED, YOU CAN REPLACE YOUR FLASHLIGHT TOO!



**1 Watt End Light**

**STUBBY II  
LED CORDLESS**

**Features**

- FOUR 1-WATT LEDs WITH 120-DEGREE ANGLE PROVIDE EQUIVALENT LIGHT PATTERN TO A FLUORESCENT LAMP AND GENERATE 480 LUMENS.
- ONE 1-WATT HIGH OUTPUT LENSED END LED PROVIDES A BRIGHT FLASHLIGHT OUT THE END
- COVERED ON/OFF SWITCH CONTROLS SIDE AND END LEDs.
- POLYCARBONATE OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- 7.4 VOLT LI-ION RECHARGEABLE BATTERY PACK OPERATES THE LIGHT FOR 5-6 HOURS STRAIGHT WHEN FULLY CHARGED.
- "UNIVERSAL" CHARGER (100VAC-240VAC, 50/60HZ) WILL DROP TO A TRICKLE CHARGE WHEN BATTER IS FULLY CHARGED.
- LITHIUM ION BATTERY RESISTS MEMORY FORMATION, WILL LAST HUNDREDS OF RECHARGES.
- CHARGER MEETS CEC (CALIFORNIA COMPLIANT)
- DISPOSE OF LITHIUM-ION BATTERY PACKS IN COMPLIANCE WITH LOCAL LAWS.



**Model No. 2302-0011**

Model No.	Description	Case Qty.	Case Weight
<b>2302-0011</b>	Stubby II Cordless, with charger, with one battery pack	4	10 lbs.
<b>2302-0012</b>	Stubby II Cordless, with charger, with two battery packs	4	12 lbs.
<b>5000-1639</b>	Battery pack, rechargeable, 7.4 L-ion	1	.6 lbs.
<b>5000-1618</b>	Battery Charger (100vac-240vac 50/60hz) for Li-ion batteries	1	.4 lbs.



RANGING FROM 1,200 TO 7,200 LUMENS, THE 110, 210 AND 310 SERIES LIGHTS DELIVER WHAT YOU NEED, LOTS OF LIGHT! OPTIONAL HANGING STRAPS, HOOKS OR MAGNETIC MOUNTS MAKE THESE LIGHTS EXTREMELY VERSATILE. DON'T GO TO WORK WITHOUT THESE INDUSTRIAL GRADE LIGHTS. YOU CAN'T AVOID DANGER IF YOU DON'T SEE IT COMING!



110 Series Lighted



210 Series Lighted



310 Series Lighted

## INDUSTRIAL LIGHTING



**SERIES 210**  
**Model No. 2020-4000**



**SERIES 110**  
**Model No. 2010-4001**

### Features

- 110 SERIES LED LIGHTS HAVE A SINGLE ROW OF LEDs AND RANGE FROM 1200 TO 2400 LUMENS.
- 210 SERIES LED LIGHTS HAVE TWO ROWS OF LEDs AND RANGE FROM 2400 TO 4800 LUMENS.
- 310 SERIES LIGHTS HAVE THREE ROWS OF LEDs AND RANGE FROM 3600 TO 7200 LUMENS.
- ALL THREE SERIES LIGHTS DELIVER 5000K BRIGHT WHITE LIGHT AND ARE RATED TO 50,000-HOUR LIFE.
- INLINE ON-OFF SWITCH IS PROTECTED BY RUBBER BOOT.
- THICK POLYCARBONATE OUTER TUBE IS EXTREMELY DURABLE.
- ANTI-ROLL SOFT END CAPS ABSORB IMPACTS WHEN THE LIGHT IS DROPPED- UNIVERSAL DRIVER INSIDE THE LIGHT FIXTURE WILL OPERATE ON 120VAC-240VAC, 50/60 HZ POWER.
- OIL RESISTANT, WATERTIGHT, COLD WEATHER RATED SJEOW CORD WITH GROUNDED PLUG.

### CORD MODELS

Model No.	Description	Lumens	Fixture Length	Cord Gauge/Type	Cord Length	Case Qty.	Case Weight
2010-4001	110 Series LED, 10 Watt	1200	28"	16/3 SJEOW	25'	4	28 lbs
2020-4001	110 Series LED, 20 Watt	2400	51"	16/3 SJEOW	25'	4	39 lbs
2020-4000	210 Series LED, 20 Watt	2400	28"	16/3 SJEOW	25'	4	28 lbs
2040-4000	210 Series LED, 40 Watt	4800	51"	16/3 SJEOW	25'	4	39 lbs
2030-4002	310 Series LED, 30 Watt	3600	28"	16/3 SJEOW	25'	4	30 lbs
2060-4001	310 Series LED, 60 Watt	7200	51"	16/3 SJEOW	25'	4	43 lbs



**BUILT WITH PRIDE  
IN THE U.S.A.**

RANGING FROM 1,200 TO 7,200 LUMENS, THE 110, 210 AND 310 SERIES MACHINE LIGHTS DELIVER MORE LIGHT TO THE WORK SURFACE. OPTIONAL MAGNETIC MOUNTS, DIRECT MOUNT GRIPS AND MACHINE MOUNT GRIPS MAKE MOUNTING THESE LIGHTS EASY. DON'T GO TO WORK WITHOUT THESE INDUSTRIAL GRADE LIGHTS. PRECISION WORK DEMANDS QUALITY LIGHT!



**110 Series Lighted**



**210 Series Lighted**



**310 Series Lighted**

**Features**

- 110 SERIES LED LIGHTS HAVE A SINGLE ROW OF LEDs AND RANGE FROM 1200 TO 2400 LUMENS.
- 210 SERIES LED LIGHTS HAVE TWO ROWS OF LEDs AND RANGE FROM 2400 TO 4800 LUMENS.
- 310 SERIES LIGHTS HAVE THREE ROWS OF LEDs AND RANGE FROM 3600 TO 7200 LUMENS.
- ALL THREE SERIES LIGHTS DELIVER 5000K BRIGHT WHITE LIGHT AND ARE RATED TO 50,000-HOUR LIFE.
- AUTO ON – APPLY POWER TO THE LIGHT TO TURN ON.
- THICK POLYCARBONATE OUTER TUBE IS EXTREMELY DURABLE.
- MODELS ARE AVAILABLE WITH POLYCARBONATE OUTER TUBE OR X-TREME SHIELD CHEMICAL RESISTANT OUTER TUBE.
- UNIVERSAL DRIVER INSIDE THE LIGHT FIXTURE WILL OPERATE ON 120VAC-240VAC, 50/60 HZ POWER.
- OIL RESISTANT, WATERTIGHT SJTOW CORD WITH GROUNDED PLUG

**MACHINE LIGHTING**



**SERIES 210  
Model No. 2020-3015**



**SERIES 110  
Model No. 2020-3003**

**CORD MODELS**

Model No.	Model No. X-Treme Shield	Description	Lumens	Fixture Length	Cord Gauge/Type	Cord Length	Case Qty.	Case Weight
2010-3000	2010-3001	110 Series LED, 10 Watt	1200	27"	16/3 SJTOW-A	25'	4	28 lbs
2020-3003	2010-3012	110 Series LED, 20 Watt	2400	51"	16/3 SJTOW-A	25'	4	39 lbs
2020-3015	2020-3016	210 Series LED, 20 Watt	2400	27"	16/3 SJTOW-A	25'	4	28 lbs
2040-3000	2040-3001	210 Series LED, 40 Watt	4800	51"	16/3 SJTOW-A	25'	4	39 lbs
2030-3006	2030-3005	310 Series LED, 30 Watt	3600	27"	16/3 SJTOW-A	25'	4	30 lbs
2060-3002	2060-3001	310 Series LED, 60 Watt	7200	51"	16/3 SJTOW-A	25'	4	43 lbs

45  
45

FLUORESCENT  
WORKLIGHTS

# SAFTLITE®

By General Mfg., Inc.

YOU ASKED FOR A TOUGH LIGHT THAT WOULD GET LIGHT INTO TIGHT SPACES AND GENERAL MANUFACTURING DELIVERED! THE STUBBY II WAS DEVELOPED TO GET LIGHT INTO TIGHT SPACES BY INCORPORATING A CLEAR LENS AND LAMP CUSHION AT THE END OF THE LIGHT FIXTURE. AS WITH THE ORIGINAL STUBBY, THE STUBBY II COMES WITH A ROUGH SERVICE FLUORESCENT LAMP. SOFT BUMPERS, LAMP CUSHION, AND THICK-WALLED OUTER TUBE MAKE THE STUBBY II UNBEATABLE FOR DURABILITY.



**Model No. 1113-2500**

## COMPACT FLUORESCENT STUBBY II



**Model No. 3613-4001**

### Features

#### HEAVY DUTY STUBBY II®

- 13-WATT ROUGH SERVICE PLS 13 FLUORESCENT LAMP PRODUCES 825 LUMENS OF BRIGHT 5000K COLORED LIGHT.
- LAMP IS RATED FOR 10,000 HOURS.
- AVAILABLE WITH STANDARD ROUGH DUTY POLYCARBONATE OR CHEMICAL RESISTANT X-TREME SHIELD™ OUTER TUBE.
- SPRING STEEL HOOK IS VIRTUALLY UNBREAKABLE.
- ON-OFF SWITCH IN HANDLE IS PROTECTED BY SOFT HANDLE GRIP.
- SOFT BUMPERS AND LAMP CUSHION HELP PROTECT THE LAMP.

### CORD MODELS

Model No. Std. Tube	Model No. X-Treme Shield	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Cord Specs	Case Qty.	Case Weight
1113-0101	1113-0130	Stubby II	No	N/A	Yes	1'	16/3 SJTOW-A	12	16 lbs.
1113-0600	1113-0131	Stubby II	Yes	12 amps	Yes	1'	16/3 SJTOW-A	12	18 lbs.
1113-2500	1113-2576	Stubby II	No	N/A	Yes	25'	18/2 SJTOW-A	12	32 lbs.
1113-5000	1113-5033	Stubby II	No	N/A	Yes	50'	18/2 SJTOW-A	12	44 lbs.
1113-5001	1113-5034	Stubby II	Yes	12 amps	Yes	50'	16/3 SJTOW-A	12	70 lbs.
1113-2502	1113-2577	Stubby II	Yes	12 amps	Yes	25'	16/3 SJTOW-A	12	45 lbs.

### REEL MODELS

Model No. Std. Tube	Model No. X-Treme Shield	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Pigtail Length	Cord Specs	Case Qty.	Case Weight
3613-3500	3613-3523	Stubby II Auto Reel	No	N/A	Yes*	40' 16/3	2' 16/3	SJTOW-A	4	41 lbs.
3613-4000	3613-4077	Stubby II	No	N/A	Yes	40' 18/2	2' 16/3	SJTOW-A	4	38 lbs.
3613-4001	3613-4075	Stubby II	Yes	12 amps	Yes	40' 16/3	2' 16/3	SJTOW-A	4	44 lbs.

\*SWITCH IS LOCATED ON THE REEL. PULL LIGHT DOWN TO TURN ON, RETRACT TO TURN LIGHT OFF.



**BUILT WITH PRIDE  
IN THE U.S.A.**

FROM OUR COMPACT STUBBY FLUORESCENT LIGHT, UP TO OUR 25-WATT FLUORESCENT SAF-T-LITE®, YOU CAN BE ASSURED THESE LIGHTS ARE DESIGNED TO LAST! THE ON-OFF SWITCH LOCATED UNDER THE DOMED END CAP IS PROTECTED FROM DIRT AND MOISTURE. THE POLYCARBONATE OUTER TUBE IS BREAK RESISTANT. SOFT END CAPS AT EACH END HELP ABSORB IMPACTS DURING ROUGH USE.

**COMPACT FLUORESCENT  
STUBBY, 15 & 25 WATT**



**Model No. 1413-2500**

**Model No. 1215-2500**



**Model No. 1225-2500**

**Features**

- 13-WATT STUBBY®**
  - 10.5" COMPACT LENGTH.
  - ROUGH SERVICE BULB IS 10X MORE IMPACT RESISTANT THAN STANDARD BULBS AND CONTAINS ONLY TRACE MERCURY.
  - LIGHT OUTPUT IS 825 LUMENS OF BRIGHT 5000K COLORED LIGHT.
  - LAMP IS RATED FOR 10,000 HOURS.
- 15-WATT SAF-T-LITE®**
  - 22' LIGHT STRETCHES LIGHT OVER A LARGER AREA.
  - LIGHT OUTPUT IS 870 LUMENS OF BRIGHT 4100K COLORED LIGHT.
  - F15T8CW LAMP IS RATED FOR UP TO 7500 HOURS.
  - LAMP IS ULTRA-COOL OPERATING.
- 25-WATT SAF-T-LITE®**
  - 45" LIGHT MAXIMIZES LARGE LIGHT PATTERN.
  - LIGHT OUTPUT IS 2125 LUMENS OF BRIGHT 4100K COLORED LIGHT.
  - F25T8CW LAMP IS RATED FOR UP TO 20,000 HOURS.
  - LAMP IS COOL OPERATING.

**CORD MODELS**

Model No. Std. Tube	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Cord Length	Cord Specs	Case Qty.	Case Weight
1413-2500	Stubby	No	N/A	Yes	25'	18/2 SJTOW-A	12	36 lbs.
1413-2501	Stubby	No	N/A	No	25'	18/2 SJTOW-A	12	36 lbs.
1413-5000	Stubby	No	N/A	Yes	50'	18/2 SJTOW-A	12	72 lbs.
1215-2500	15 Watt	No	N/A	Yes	25'	18/2 SJTOW-A	12	43 lbs.
1225-2500	25 Watt	No	N/A	Yes	25'	16/3 SJTOW-A	4	20 lbs.
1225-2501	25 Watt w Straps*	No	N/A	Yes	25'	16/3 SJTOW-A	4	23 lbs.

\* 25 W HOODLIGHT COMES WITH ADJUSTABLE HANGING KIT (5000-0851) ON PG 24.

**REEL MODELS**

Model No. Std. Tube	Description	Switch Y/N	Retracting Cord Specs	Pigtail Cord Specs	Cord Specs	Case Qty.	Case Weight
3215-4000	15-Watt, 40' Reel	Yes	40' 18/2	2' 16/3	SJTOW-A	4	44 lbs.
3313-4000	Stubby, 40' Reel	Yes	40' 18/2	2' 16/3	SJTOW-A	4	39 lbs.
3413-4000	Stubby Auto Reel	Yes*	40' 18/2	2' 16/3	SJTOW-A	4	39 lbs.

\* SWITCH IS LOCATED ON THE REEL. PULL LIGHT DOWN TO TURN ON, RETRACT TO TURN LIGHT OFF.

FLUORESCENT  
WORK LIGHTS

# SAFTLITE®

By General Mfg., Inc.

THE MID SIZE REEL BY GENERAL MANUFACTURING IS AVAILABLE WITH THE STUBBY® OR STUBBY II®. YOU CAN HARDLY GO WRONG! THE REEL IS DESIGNED AS A PORTABLE REEL, OR IT CAN BE PERMANENTLY MOUNTED ON THE CEILING OR WALL. THE STEEL MOUNTING BRACKET WITH LOCKING PIN AND SAFETY CHAIN ENSURE THE REEL WILL STAY MOUNTED IN PLACE.

**Smooth Roller Guides**



**Optional  
Tool Tap Available**



**Stubby Available**



## MID SIZE REEL FLUORESCENT

### Features

- 50' 16-GAUGE SJTW RETRACTING CORD.
- 27" 12/3 SJTW POWER INLET CORD (PIGTAIL) HAS MOLDED NEMA 5-15P GROUNDED PLUG.
- ROLLERS AT THE OPENING OF THE REEL ENSURE SMOOTH PAYOUT AND TAKE UP.
- SAFETY OF A STEEL MOUNTING BRACKET, LOCKING PIN, AND SAFETY CHAIN.
- REEL CAN BE EASILY REMOVED FROM THE MOUNTING BRACKET AND TAKEN TO JOB SITE.
- PLASTIC REEL HOUSING IS MADE OF A SUPER TOUGH BLENDED PLASTIC.
- MODELS ARE AVAILABLE WITH OR WITHOUT TOOL TAP.



**Model No. 2213-5007**

### REEL MODELS

Model No. Std. Tube	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Retracting Cord Specs	Pigtail Cord Specs	Cord Specs	Case Qty.	Case Weight
2213-5007	Stubby II	No	N/A	Yes	50' 16/3	2' 16/3	SJTOW-A	2	32 lbs.
2213-5014	Stubby	No	N/A	Yes	50' 16/3	2' 16/3	SJTOW-A	2	31 lbs.
2213-5005	Stubby II	Yes	12 amps	Yes	50' 16/3	2' 16/3	SJTOW-A	2	30 lbs.



**BUILT WITH PRIDE  
IN THE U.S.A.**

SAF-T-LITE® SERIES 4000 REELS ARE DESIGNED TO LAST IN COMMERCIAL AND INDUSTRIAL ENVIRONMENTS. THE REEL COMES WITH RUGGED STEEL FRAME WITH POWDER COAT FINISH, INDUSTRIAL GRADE COLLECTOR RING, OIL RESISTANT, WATERTIGHT CORD, AND CHOICE OF THE STUBBY® OR STUBBY II®. AN ADJUSTABLE GUIDE ARM WITH ROLLERS ALLOWS THE USER TO MOUNT THE REEL ON THE CEILING, TO THE WALL, OR ON A WORK BENCH.

# SERIES 4000 FLUORESCENT LIGHTS



**Adjustable Guide Arm  
Mount to Ceilings,  
Walls, or Benches.**



**Optional  
Tool Tap Available**



**Model No. 4050-2334**



**Stubby II Available**

### Features

- ADJUSTABLE GUIDE ARM FOR WALL, CEILING OR BENCH MOUNT.
- GUIDE ARM HAS ROLLERS TO ALLOW SMOOTH PAYOUT AND TAKE-UP OF CORD.
- SJTOW CORD IS OIL RESISTANT AND WATERTIGHT.
- 5.5' POWER INLET CORD COMES WITH NEMA 5-15P GROUNDED PLUG.
- BALL STOP ALLOWS USER TO SET HANG DOWN HEIGHT OF THE RETRACTING CORD.
- STUBBY II® IS AVAILABLE WITH OR WITHOUT TOOL TAP.

### REEL MODELS

Model No. Std. Tube	Description	Outlet Y/N	Outlet Rating	Switch Y/N	Retracting Cord Specs	Pigtail Cord Specs	Cord Specs	Case Qty.	Case Weight
4050-2334	Stubby	No	N/A	Yes	50' 16/2	5.5' 16/3	SJTOW-A	1	32 lbs.
4050-2669	Stubby II	No	N/A	Yes	50' 16/2	5.5' 16/3	SJTOW-A	1	31 lbs.
4050-2670	Stubby II	Yes	10 amps	Yes	50' 16/3	5.5' 16/3	SJTOW-A	1	30 lbs.

FLUORESCENT  
WORK LIGHTS

# SAFTLITE®

By General Mfg., Inc.

THESE ARE THE LIGHTS THAT EVERY MAINTENANCE DEPARTMENT MUST HAVE! SAF-T-LITE® TWIN TUBE PORTABLE LIGHTS ARE BRIGHT, COMPACT AND TOUGH! THE EXTRA THICK TOUGH-SHIELD™ OUTER TUBE AND THICK HEXAGONAL END CAPS WITHSTAND THE HARD USE THAT INDUSTRY DEMANDS.

SEE PAGE 23 FOR MOUNTING/HANGING OPTIONS.



**Vertical Hanging Options**  
5000-1055



**Horizontal Hanging Options**  
5000-1296

## TWIN TUBE MAINTENANCE LIGHTS



**Magmount Hanging Options**  
5000-1077



**Model No. 1624-2016**

### Features

- 24 WATT LAMP PRODUCES 1800 LUMENS OF LIGHT AND IS RATED AT 14,000 HOURS.
- 36 WATT LAMP PRODUCES 2900 LUMENS OF LIGHT AND IS RATED AT 14,000 HOURS.
- 50 WATT LAMP PRODUCES 3750 LUMENS OF LIGHT AND IS RATED AT 14,000 HOURS.
- TOUGH SHIELD™ OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- 16/3 SJEOW CORD IS OIL RESISTANT, WATERTIGHT AND COLD WEATHER RATED.
- 120VAC ELECTRONIC BALLAST IS PROTECTED INSIDE THE LIGHT FIXTURE.
- 24 AND 36 WATT MODELS COME WITH A VERTICAL HANGING HOOK, 50 WATT MODELS COME WITH HORIZONTAL HOOK.
- THICK HEXAGONAL SHAPED END CAPS PROVIDE IMPACT PROTECTION AND PREVENT THE LIGHT FROM ROLLING.
- PROTECTED INLINE ON-OFF SWITCH.
- ALL PARTS ARE MOUNTED TO A FULL-LENGTH ALUMINUM EXTRUDED BACKBONE FOR EXTRA DURABILITY AND EASE OF SERVICE.

### CORD MODELS

Model No.	Description	Lumen Output	Cord	Voltage	Anti-Strobe	Light Fixture Dimensions		Case Qty.	Case Weight
						Length	Diameter		
1624-2016	24 Watt, 25' Cord, Ballast in Head	1800	16/3 SJEOW-A	120V-60Hz	Yes	20.25"	4"	4	28 lbs.
1624-2017	24 Watt, 50' Cord, Ballast in Head	1800	16/3 SJEOW-A	120V-60Hz	Yes	20.25"	4"	4	32 lbs.
1636-2012	36 Watt, 25' Cord, Ballast in Head	2900	16/3 SJEOW-A	120V-60Hz	Yes	24.75"	4"	4	29 lbs.
1636-2013	36 Watt, 50' Cord, Ballast in Head	2900	16/3 SJEOW-A	120V-60Hz	Yes	24.75"	4"	4	33 lbs.
1650-3015	50 Watt, 25' Cord, Ballast in Head	3750	16/3 SJEOW-A	120V-60Hz	Yes	33.25"	4"	4	33 lbs.
1650-3016	50 Watt, 50' Cord, Ballast in Head	3750	16/3 SJEOW-A	120V-60Hz	Yes	33.25"	4"	4	37 lbs.



**BUILT WITH PRIDE  
IN THE U.S.A.**

RANGING FROM 10.5" LONG UP TO 45" LONG, SAF-T-LITE COMPACT MACHINE LIGHTS ARE ONLY 2" IN DIAMETER. THE FLUORESCENT LAMPS ARE VIBRATION RESISTANT, MAKING THEM PERFECT FOR STAMPING PRESSES AND OTHER HIGH IMPACT EQUIPMENT. THE SMALL DIAMETER ALLOWS THEM TO BE USED FOR BENCH, CABINET, OR WORKSTATION LIGHTING.



**Magnmounts**



**Water Tight Clamps**

**MACHINE LIGHTS  
STUBBY, 15-WATT, AND  
25-WATT**

**Features**

- 13-WATT STUBBY®**
- 10.5" LENGTH IS COMPACT ENOUGH FOR TIGHT SPACES.
  - 13 WATT ROUGH SERVICE LAMP IS 10X MORE IMPACT RESISTANT THAN STD. FLUORESCENT LAMPS.
  - LAMP PRODUCES 825 LUMENS OF 5000K COLORED LIGHT AND IS RATED AT 10,000 HOURS.
  - PROTECTED ON OFF SWITCH IS LOCATED UNDER THE DOMED END CAP.
  - CLAMP KIT KEEPS MOISTURE AND DUST OUT OF THE FIXTURE.
  - COMES STANDARD WITH TWO MAGNETIC MOUNTS.
  - 25' 16/3 SJTOW CORD WITH MOLDED NEMA 5-15P GROUNDED PLUG AND BALLAST INLINE.
- 15-WATT SAF-T-LITE®**
- 22" LENGTH SPREADS THE LIGHT OVER A LARGER AREA.
  - 13 WATT ROUGH SERVICE LAMP IS 10X MORE IMPACT RESISTANT THAN STD. FLUORESCENT LAMPS.
  - LAMP PRODUCES 825 LUMENS OF 4100K COLORED LIGHT AND IS RATED AT 10,000 HOURS.
  - PROTECTED ON OFF SWITCH IS LOCATED UNDER THE DOMED END CAP.
  - CLAMP KIT KEEPS MOISTURE AND DUST OUT OF THE FIXTURE.
  - COMES STANDARD WITH TWO MAGNETIC MOUNTS.
  - 25' 16/3 SJTOW CORD WITH MOLDED NEMA 5-15P GROUNDED PLUG AND BALLAST INLINE.
- 25-WATT SAF-T-LITE®**
- 45" LENGTH SPREADS THE LIGHT OVER THE LARGEST AREA.
  - LAMP PRODUCES 2125 LUMENS OF 4100K COLORED LIGHT AND IS RATED AT 14,000 HOURS.
  - PROTECTED ON OFF SWITCH IS LOCATED UNDER THE DOMED END CAP.
  - CLAMP KIT KEEPS MOISTURE AND DUST OUT OF THE FIXTURE.
  - COMES STANDARD WITH TWO MAGNETIC MOUNTS.
  - 25' 16/3 SJTOW CORD WITH MOLDED NEMA 5-15P GROUNDED PLUG AND BALLAST INLINE.



**Model No. 1413-2591**



**Model No. 1215-2540**



**Model No. 1225-2512**

**CORD MODELS**

Model No.	Description	Switch	Fixture	Cord Specifications		Case	Case	
Std. Tube		Y/N	Length	Cord Length	Gauge/Cond	Type	Qty.	Weight
1413-2591	13-Watt Stubby®	Yes	10.5"	25'	16/3	SJTOW-A	12	38 lbs.
1215-2540	15-Watt Saf-T-Lite®	Yes	22"	25'	16/3	SJTOW-A	12	48 lbs.
1225-2512	25-Watt Saf-T-Lite®	Yes	45"	25'	16/3	SJTOW-A	4	32 lbs.

WHETHER YOU NEED A SUPER BRIGHT LIGHT IN A SMALL AREA OR AN EVEN LIGHT SPREAD OVER A LARGER WORK SURFACE, SAFT-LITE FLUORESCENT MACHINE LIGHTS ARE THE INDUSTRY STANDARD. ALL MODELS ARE INSTANT ON WHEN POWER IS APPLIED TO THEM. AN OPTIONAL ON-OFF SWITCH IS AVAILABLE AS WELL. VARIOUS FIXTURE LENGTHS AND OUTER TUBES ARE AVAILABLE.

SEE PAGE 23 FOR MOUNTING/HANGING OPTIONS.

## Features

### SINGLE TUBE LIGHTS

- 25 WATT LAMP PRODUCES 2125 LUMENS OF LIGHT AND IS RATED AT 20,000 HOURS.
- 32 WATT LAMP PRODUCES 2800 LUMENS OF LIGHT AND IS RATED AT 20,000 HOURS.
- TWIN 54 WATT LAMP PRODUCES 10,000 LUMENS OF LIGHT AND IS RATED AT 20,000 HOURS.
- TOUGH SHIELD™ OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- 16/3 SJTO CORD IS OIL RESISTANT, WATERTIGHT AND COLD WEATHER RATED.
- 120VAC ELECTRONIC BALLAST IS PROTECTED INSIDE THE LIGHT FIXTURE.
- X-TREME SHIELD™ OUTER TUBE IS CHEMICAL RESISTANT; TOUGH-SHIELD™ OUTER TUBE IS EXTREMELY TOUGH TO HARD KNOCKS.
- 12 AND 24VAC AND VDC MODELS ARE AVAILABLE.
- A VARIETY OF MOUNTING OPTIONS ARE AVAILABLE.

### TWIN TUBE LIGHTS

- 24 WATT LAMP PRODUCES 1800 LUMENS OF LIGHT AND IS RATED AT 14,000 HOURS.
- 36 WATT LAMP PRODUCES 2900 LUMENS OF LIGHT AND IS RATED AT 14,000 HOURS.
- 50 WATT LAMP PRODUCES 3750 LUMENS OF LIGHT AND IS RATED AT 14,000 HOURS.
- TOUGH SHIELD™ OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- 16/3 SJTO CORD IS OIL RESISTANT, WATERTIGHT AND COLD WEATHER RATED.
- 120VAC ELECTRONIC BALLAST IS PROTECTED INSIDE THE LIGHT FIXTURE.
- X-TREME SHIELD™ OUTER TUBE IS CHEMICAL RESISTANT; TOUGH-SHIELD™ OUTER TUBE IS VIRTUALLY UNBREAKABLE.
- 12 AND 24VAC AND VDC MODELS ARE AVAILABLE.

## FLUORESCENT MACHINE LIGHTS

Model No. 1625-3026



Model No. 1624-2001



## CORD MODELS - TWIN TUBE

Model No.	Description	Outer Tube	Cord	Voltage	Anti-Strobe	Light Fixture Dimensions		Case Qty.	Case Weight
						Length	Diameter		
1624-2001	24 Watt, 25' Cord, Ballast in Head	Tough-Shield™	16/3 SJTOW-A	120V-60Hz	Yes	20.75"	2.625"	4	24 lbs.
1624-2013	24 Watt, 25' Cord, Ballast in Head	X-Treme Shield™	16/3 SJTOW-A	120V-60Hz	Yes	20.75"	2.625"	4	24 lbs.
1636-2000	36 Watt, 25' Cord, Ballast in Head	Tough-Shield™	16/3 SJTOW-A	120V-60Hz	Yes	25.25"	2.625"	4	25 lbs.
1636-2011	36 Watt, 25' Cord, Ballast in Head	X-Treme Shield™	16/3 SJTOW-A	120V-60Hz	Yes	25.25"	2.625"	4	25 lbs.
1650-3000	50 Watt, 25' Cord, Ballast in Head	Tough-Shield™	16/3 SJTOW-A	120V-60Hz	Yes	33.75"	2.625"	4	29 lbs.
1650-3014	50 Watt, 25' Cord, Ballast in Head	X-Treme Shield™	16/3 SJTOW-A	120V-60Hz	Yes	33.75"	2.625"	4	29 lbs.

## CORD MODELS - SINGLE TUBE

Model No.	Description	Outer Tube	Cord	Voltage	Anti-Strobe	Light Fixture Dimensions		Case Qty.	Case Weight
						Length	Diameter		
1625-3026	25 Watt, 25' Cord, Ballast in Head	Tough-Shield™	SJTOW-A	120V-60Hz	Yes	48.00"	2.625"	4	41 lbs.
1625-3042	25 Watt, 25' Cord, Ballast in Head	X-Treme Shield™	SJTOW-A	120V-60Hz	Yes	48.00"	2.625"	4	41 lbs.
1632-4007	32 Watt, 25' Cord, Ballast in Head	Tough-Shield™	SJTOW-A	120V-60Hz	Yes	60.25"	2.625"	4	42 lbs.
1632-4018	32 Watt, 25' Cord, Ballast in Head	X-Treme Shield™	SJTOW-A	120V-60Hz	Yes	60.25"	2.625"	4	42 lbs.
1654-8007	Twin 54 Watt, 25' Cord, Ballast in Head	X-Treme Shield™	SJTOW-A	120V-60Hz	Yes	112.00"	2.625"	4	60 lbs.
1654-8008	Twin 54 Watt, 25' Cord, Ballast in Head	Tough-Shield™	SJTOW-A	120V-60Hz	Yes	112.00"	2.625"	4	60 lbs.

\*NOTE: TWO MOUNTS ARE REQUIRED PER LIGHT.



**BUILT WITH PRIDE  
IN THE U.S.A.**

WHEN GOING IN TO AN EXPLOSIVE AREA, YOU DON'T NECESSARILY WANT TO GO IN WITH THE LOWEST BIDDER'S LIGHT. YOU WANT TO GO IN WITH A LIGHT YOU CAN TRUST. SAF-T-LITE EXPLOSION-PROOF LIGHTS HAVE BEEN BUILT SINCE THE 1940's. THE TECHNOLOGY IS TRIED AND TRUE AND THE DURABILITY IS THERE TOO! AVAILABLE AS LIGHT FIXTURE LESS CORD, WITH 25' OR 50' CORD, OR ON NON-EXPLOSION-PROOF REEL, THERE ARE PLENTY OF OPTIONS TO CHOOSE. USE SAF-T-LITE AND BE SAFE!

**EXPLOSION PROOF**

**XP162 INCANDESCENT EXPLOSION PROOF LIGHT**

- 100 WATT LIGHT BULB AND GLASS GLOBE ARE PROTECTED BY NON-SPARKING HIGH IMPACT ALUMINUM ALLOY GUARD.
- NO REFLECTOR - 360 DEGREE LIGHTING.
- RATED FOR USE IN CLASS 1, DIV 1, GROUP C & D AND CLASS 2, DIV 1 GROUP F & G LOCATIONS.

**XP87B FLUORESCENT EXPLOSION PROOF LIGHT**

- 26 WATT FLUORESCENT PRODUCES 1800 LUMENS OF BRIGHT LIGHT AND IS RATED AT 10,000 HOURS.
- GUARD, HANDLE, AND HOOK ARE ALL MADE OF ZYTEL 801ST SUPER TOUGH CORROSION RESISTANT MATERIAL.
- RATED FOR USE IN CLASS 1, DIV 1, GROUP C & D AND CLASS 2, DIV 1 GROUP F & G LOCATIONS.

**XP99 SEALED BEAM EXPLOSION PROOF LIGHT**

- 50 WATT SEALED BEAM LAMP IS PROTECTED BY AN ALUMINUM GUARD.
- PHENOLIC HANDLE IS EXTREMELY DURABLE.
- UNIT IS RATED FOR CLASS 1, DIV 1, GROUP D LOCATIONS.



**A. XP162 Incandescent Explosion Proof Light**

**B. XP87B Fluorescent Explosion Proof Light**

**C. XP99 Sealed Beam Explosion Proof Light**

Model No.	Description	Switch in Lighthead	Hazardous Location Rating	Cord Length	Cord Specs	Lamp Type	Lamp Size	Case Qty.	Case Weight
5165-9684	XP87B Head Kit, 120 Volt	No	Class 1, Group C & D Class 2, Group F & G	-	-	PLC	26 Watt	9	38 lbs.
4425-4009	XP87B, less Plug	No	Class 1, Group C & D Class 2, Group F & G	25'	16/3 SO	PLC	26 Watt	4	25 lbs.
4450-4008	XP87B, less plug	No	Class 1, Group C & D Class 2, Group F & G	50'	16/3 SO	PLC	26 Watt	4	33 lbs.
4550-2005	XP87B, Non-Explosionproof Auto Reel*	No	Class 1, Group C & D Class 2, Group F & G	50'	16/3 SO	PLC	26 Watt	1	44 lbs.
5165-9555	XP162 Head Kit, 120 Volt	No	Class 1, Group C & D	-	-	Bulb	100 Watt	9	40 lbs.
4325-4000	XP162, less Plug	No	Class 1, Group C & D	25'	16/3 SO	Bulb	100 Watt	4	26 lbs.
4350-4000	XP162, less Plug	No	Class 1, Group C & D	50'	16/3 SO	Bulb	100 Watt	4	34 lbs.
4550-3002	XP162, Non-Explosionproof Auto Reel*	No	Class 1, Group C & D	50'	16/3 SO	Bulb	100 Watt	1	44 lbs.
5165-9582	XP99 Head Kit, 12 Volt	No	Class 1, Group D	-	-	Sealed Beam	50 Watt	9	36 lbs.
4325-1500	XP99, less Plug	No	Class 1, Group D	25'	16/3 SO	Sealed Beam	50 Watt	4	24 lbs.
4350-1500	XP99, less Plug	No	Class 1, Group D	50'	16/3 SO	Sealed Beam	50 Watt	4	31 lbs.

**SWITCH IS LOCATED ON THE REEL. PULL LIGHT DOWN TO TURN ON, RETRACT TO TURN LIGHT OFF.**

ENTERING AN AREA THAT IS WET OR ENCLOSED SUCH AS A TANK OR VAT? CONFINED SPACE AREAS REQUIRE SPECIAL EQUIPMENT... BECAUSE YOUR LIFE CAN DEPEND ON IT! SAF-T-LITE CONFINED SPACE ENTRY LIGHTS WITH DEDICATED TRANSFORMERS MEET OSHA REQUIREMENTS WHEN ENTERING WET OR CONFINED AREAS. 120V POWER PASSES THROUGH A TRANSFORMER THAT DELIVERS SAFE 12-VOLT POWER TO THE LIGHT FIXTURE. MODELS ARE AVAILABLE WITH EXPLOSION PROOF FIXTURES OR WATERTIGHT FIXTURE. IF FLAMMABLE GASSES OR DUSTS ARE PRESENT, CHOOSE ONE OF THE XP LIGHTS. IF WATER IS THE CONCERN, THE STUBBY II LIGHT FIXTURE IS WATERTIGHT AS WELL AS LOW VOLTAGE.

## CONFINED SPACE ENTRY - DEDICATED

**MODEL No. 2811-2119 STUBBY II** – EQUAL TO A 75-WATT LIGHT BULB, THE STUBBY II FLUORESCENT LIGHT IS WATERTIGHT (NOT SUBMERSIBLE), COMPACT AND DURABLE! THE POLYCARBONATE OUTER TUBE AND SPRING STEEL HOOK ARE VIRTUALLY UNBREAKABLE. A REFLECTOR INSIDE THE OUTER TUBE DIRECTS MAXIMUM LIGHT TO THE WORK SURFACE. THE ON-OFF SWITCH LOCATED UNDER THE HANDLE END CAP IS PROTECTED FROM DIRT AND MOISTURE. A MOISTURE TIGHT CLAMP KIT MAKES THE STUBBY II LIGHT FIXTURE RESISTANT TO WATER SPRAY. THIS UNIT IS NOT RATED FOR HAZARDOUS LOCATIONS REQUIRING EXPLOSION PROOF LIGHTS. MODEL 2811-2119 COMES WITH 10' PRIMARY CORD WITH NEMA 5-15P GROUNDED PLUG AND HAS A 50' 16/3 SOW SECONDARY CORD WITH STUBBY II ATTACHED. TRANSFORMER AND PLUG MUST BE KEPT OUT OF THE CONFINED SPACE WET LOCATION.



**MODEL No. 2831-2000 XP87B HAZARDOUS LOCATION LIGHT** – FOR MORE LIGHT, CHOOSE THE XP87B 26-WATT FLUORESCENT FIXTURE. EQUAL TO A 120V LIGHT BULB, THE UNIT COMES WITH A REFLECTOR, WHICH DIRECTS MAXIMUM LIGHT TO THE WORK SURFACE. THE XP87B IS RATED FOR USE IN CLASS I, DIVISION 1, GROUPS C AND D AREAS PLUS CLASS II, DIVISION 1, GROUPS F & G LOCATIONS. THE XP87B FIXTURE HOUSING IS MADE OF CORROSION RESISTANT, LIGHTWEIGHT ZYTEL SUPER TOUGH PLASTIC. MODEL 2831-2000 COMES WITH 10' PRIMARY CORD WITH NEMA 5-15P GROUNDED PLUG AND HAS A 50' 16/3 SOW SECONDARY CORD WITH XP87B ATTACHED. IN ALL CASES, THE TRANSFORMER AND PLUG MUST BE LOCATED OUTSIDE OF THE HAZARDOUS, CONFINED SPACE AREAS.

**MODEL No. 2812-1014 XP162 HAZARDOUS LOCATION LIGHT** - DESIGNED FOR CLASS I, DIV 1, GROUPS C & D HAZARDOUS LOCATIONS, THE XP162 COMES STANDARD WITH 75-WATT, 12-VOLT INCANDESCENT BULB. THE OUTER SHELL IS MADE OF A CORROSION RESISTANT, NON-SPARKING METAL AND COMES WITH ROTATING HOOK. NO REFLECTOR ON THE LIGHT FIXTURE MEANS THE XP162 WILL LIGHT UP A 360-DEGREE AREA. MODEL 2812-1014 COMES WITH 10' PRIMARY CORD WITH NEMA 5-15P GROUNDED PLUG AND HAS A 50' 16/3 SOW SECONDARY CORD WITH XP162 ATTACHED. AS WITH ALL CONFINED SPACE MODELS, THE TRANSFORMER AND PLUG MUST BE KEPT OUT OF THE HAZARDOUS, CONFINED SPACE AREA AT ALL TIMES.



**MODEL No. 2812-1020 XP99 HAZARDOUS LOCATION LIGHT** – GREAT FOR CLASS I, DIV 1, GROUP D HAZARDOUS LOCATIONS, THE XP99 COMES STANDARD WITH A 50-WATT, 12V SEALED BEAM LAMP. THE LAMP HAS A BRIGHT BEAM AT THE CENTER OF THE LIGHT PATTERN AND AN AREA FLOOD FEATURE IN THE SURROUNDING DIAMETER. AT 100,000 CANDLEPOWER, THE XP99 IS EXCELLENT FOR INSPECTING LARGE VESSELS OR VATS. THE OUTER SHELL IS MADE OF A CORROSION RESISTANT, NON-SPARKING METAL AND COMES WITH ROTATING HOOK. MODEL 2812-1020 COMES WITH 10' PRIMARY CORD WITH NEMA 5-15P GROUNDED PLUG AND HAS A 50' 16/3 SOW SECONDARY CORD WITH XP99 ATTACHED. THE TRANSFORMER AND PLUG MUST BE KEPT OUT OF THE HAZARDOUS, CONFINED SPACE.



**BUILT WITH PRIDE  
IN THE U.S.A.**

SAF-T-LITE CONFINED SPACE ENTRY LIGHTS WITH QUICK DISCONNECT TRANSFORMERS MEET OSHA REQUIREMENTS WHEN ENTERING WET OR CONFINED AREAS. 120V POWER PASSES THROUGH A TRANSFORMER THAT DELIVERS SAFE 12-VOLT POWER TO TWIST LOCK RECEPTACLES. LOW VOLTAGE LIGHT MODELS COME WITH 50' CORD AND TWIST LOCK PLUG AND ARE AVAILABLE IN EXPLOSION PROOF OR WATERTIGHT VARIATIONS. IF FLAMMABLE GASSES OR DUSTS ARE PRESENT, CHOOSE ONE OF THE XP LIGHTS. IF WATER IS THE CONCERN, THE STUBBY II IS WATERTIGHT. AT ALL TIMES KEEP THE POWER SUPPLY AND PLUG OUT OF THE HAZARDOUS OR WET LOCATIONS.

# CONFINED SPACE ENTRY - QUICK DISCONNECT

## MODEL No. 2811-2027 STUBBY II & XP87B POWER SUPPLY BOX

2811-2027 COMES WITH NEMA 4X BOX, WITH HANDLE, 10' 16/3 POWER INLET CORD AND TWO SECONDARY 6" CORDS WITH TWIST LOCK RECEPTACLES. THE ELECTRONICS IN THIS MODEL ALLOW 120V POWER INPUT AND SAFELY DELIVERS 12VDC POWER TO EACH LIGHT FIXTURE. THE USER MAY RUN UP TO TWO XP87B EXPLOSION PROOF LIGHTS OR TWO STUBBY II WET LOCATION LIGHTS AT THE SAME TIME. THE TRANSFORMER BOX AND PLUG MUST BE KEPT OUT OF WET OR HAZARDOUS CONFINED SPACE.

## MODEL No. 2812-0000 XP162 AND XP99 POWER SUPPLY BOX

2812-0000 COMES WITH NEMA 4X BOX, WITH HANDLE, 10' 16/3 SOW POWER INLET CORD AND TWO SECONDARY 6" CORDS WITH TWIST LOCK RECEPTACLES. THE ELECTRONICS IN THIS MODEL ALLOW 120V INPUT POWER AND SAFELY DELIVERS 12VDC POWER TO EACH LIGHT FIXTURE. THE USER MAY RUN ONE OR TWO XP162 LIGHTS OR ONE OR TWO XP99 LIGHTS AT THE SAME TIME. IF THE HAZARDOUS AREA IS A CLASS 1, DIV I, GROUP D AREA ONLY, ONE XP99 AND ONE XP162 LIGHT MAY BE RUN AT THE SAME TIME ON THIS UNIT. THE TRANSFORMER AND PLUG MUST BE KEPT OUTSIDE THE WET OR HAZARDOUS CONFINED SPACE.

## FEATURES - MODEL No. 1713-5017

STUBBY II - EQUAL TO A 75-WATT LIGHT BULB, THE STUBBY II, 12-VOLT FLUORESCENT LIGHT IS WATER-TIGHT (NOT SUBMERSIBLE), COMPACT AND DURABLE! THE POLYCARBONATE OUTER TUBE AND SPRING STEEL HOOK ARE VIRTUALLY UNBREAKABLE. A REFLECTOR INSIDE THE OUTER TUBE DIRECTS MAXIMUM LIGHT TO THE WORK SURFACE. THE ON-OFF SWITCH LOCATED UNDER THE HANDLE END CAP IS PROTECTED FROM DIRT AND MOISTURE. A MOISTURE TIGHT CLAMP KIT MAKES THE STUBBY II LIGHT FIXTURE RESISTANT TO WATER SPRAY. THIS UNIT IS NOT RATED FOR HAZARDOUS LOCATIONS REQUIRING EXPLOSION PROOF LIGHTS. LIGHT FIXTURE COMES WITH 50' 16/3 SOW CORD AND TWIST LOCK PLUG. TRANSFORMER AND PLUG MUST BE KEPT OUT OF THE CONFINED SPACE WET LOCATION.

## FEATURES - MODEL No. 4450-2008

XP87B - FOR MORE LIGHT, CHOOSE THE XP87B 26-WATT, 12-VOLT FLUORESCENT FIXTURE. EQUAL TO A 120V LIGHT BULB, THE UNIT COMES WITH A REFLECTOR, WHICH DIRECTS MAXIMUM LIGHT TO THE WORK SURFACE. THE XP87B IS RATED FOR USE IN CLASS I, DIVISION 1, GROUPS C AND D AREAS PLUS CLASS 2, DIVISION I, GROUPS F & G LOCATIONS. THE XP87B FIXTURE HOUSING IS MADE OF CORROSION RESISTANT, LIGHTWEIGHT ZYTEL SUPER TOUGH PLASTIC. LIGHT FIXTURE COMES WITH 50' 16/3 SOW CORD AND TWIST LOCK PLUG. IN ALL CASES, THE TRANSFORMER AND PLUG MUST BE LOCATED OUTSIDE OF THE HAZARDOUS AREAS.

## FEATURES - MODEL No. 4350-1002

XP162 - DESIGNED FOR CLASS I, DIV 1, GROUPS C & D HAZARDOUS LOCATIONS, THE XP162 COMES STANDARD WITH 75-WATT, 12-VOLT INCANDESCENT BULB. THE OUTER SHELL IS MADE OF A CORROSION RESISTANT, NON-SPARKING METAL AND COMES WITH ROTATING HOOK. NO REFLECTOR ON THE LIGHT FIXTURE MEANS THE XP162 WILL LIGHT UP A 360-DEGREE AREA. LIGHT FIXTURE COMES WITH 50' 16/3 SOW CORD AND TWIST LOCK PLUG. AS WITH ALL CONFINED SPACE MODELS, THE TRANSFORMER AND PLUG MUST BE KEPT OUT OF THE HAZARDOUS, CONFINED SPACE AREA AT ALL TIMES.

## FEATURES - MODEL No. 4350-1502

XP99 - GREAT FOR CLASS I, DIV 1, GROUP D HAZARDOUS LOCATIONS, THE XP99 COMES STANDARD WITH A 50-WATT, 12V SEALED BEAM LAMP. THE LAMP HAS A BRIGHT BEAM AT THE CENTER OF THE LIGHT PATTERN AND AN AREA FLOOD FEATURE IN THE SURROUNDING DIAMETER. AT 100,000 CANDLEPOWER, THE XP99 IS EXCELLENT FOR INSPECTING LARGE VESSELS OR VATS. THE OUTER SHELL IS MADE OF A CORROSION RESISTANT, NON-SPARKING METAL AND COMES WITH ROTATING HOOK. LIGHT FIXTURE COMES WITH 50' 16/3 SOW CORD AND TWIST LOCK PLUG. THE TRANSFORMER AND PLUG MUST BE KEPT OUT OF THE HAZARDOUS, CONFINED SPACE AREA AT ALL TIMES.



**Model No. 2811-2027**



**Model No. 1713-5017**



**Model No. 4450-2008**



**Model No. 4350-1002**



**Model No. 4350-1502**

WHEN YOU NEED TOUGH PORTABLE STRING LIGHTING, SAF-T-LITE COMMERCIAL GRADE STRING LIGHTS MAY BE THE RIGHT CHOICE FOR YOU. LIGHT ENOUGH TO BE EASILY TRANSPORTED, BUT DURABLE ENOUGH TO TAKE THE DROPS, THE 25-WATT FLUORESCENT MODEL DELIVERS A NICE SMOOTH LIGHT AT A COMPETITIVE PRICE. UP TO 18 OF THIS LIGHT MAY BE DAISY CHAINED. TO TURN THE LIGHT STRING ON, SIMPLY PLUG THE STRING INTO A 120VAC POWER SOURCE. THIS STRING LIGHT CAN BE HUNG WITH OUR ADJUSTABLE HANGING STRAP KIT OR WITH TWO OF OUR MAGMOUNTS™.

### 25 Watt Shelter Lighting



## COMMERCIAL STRING LIGHTING



Model No. 5000-1030

Adjustable Hanging Strap Kit  
with Foam Padded Hooks



Model No. 5000-0851



Model No. 1225-0500

### Features

- 25-WATT LAMP DELIVERS 2125 LUMENS OF BRIGHT 5000K COLORED LIGHT.
- LAMP IS RATED FOR UP TO 14,000 HOURS AND IS VERY COOL OPERATING.
- DURABLE POLYCARBONATE OUTER TUBE PROTECTS THE LAMP.
- SOFT END CAPS PROVIDE IMPACT PROTECTION.
- BOOTED NEMA 5-15P PLUG AND RECEPTACLE PROVIDE MOISTURE TIGHT FIXTURE.
- UNIT IS AN INSTANT START, PLUG IN TO POWER TO TURN LIGHT ON, UNPLUG TO TURN LIGHT OFF.
- CLAMP KIT KEEPS MOISTURE AND DUST OUT OF THE LIGHT FIXTURE.
- HORIZONTAL HANGING HOOKS ARE INCLUDED.

### FLUORESCENT MODELS

Model No.	Description	No. of Lights Stringable	Lumen Output	Fixture Length	Input Cord Length	Output Cord Length	Cord Specs	Case Qty.	Case Weight
1225-0500	25-Watt	20	2125	45"	5'	1'	18/3 SJTOW	4	22 lbs.



**BUILT WITH PRIDE  
IN THE U.S.A.**

WHEN YOU NEED TOUGH PORTABLE STRING LIGHTING, SAF-T-LITE® INDUSTRIAL GRADE STRING LIGHTS MAY BE THE RIGHT CHOICE FOR YOU. THESE LIGHTS ARE FOUND ON MILITARY BASES AROUND THE WORLD. IF THE US MILITARY THINKS THEY ARE TOUGH ENOUGH, THEY WILL BE PERFECT FOR YOUR FACILITY TOO!

SEE PAGE 23 FOR HANGING OPTIONS.

# INDUSTRIAL STRING LIGHTING



**Model No. 1650-5068**



**Model No. 1625-5025**

## Features

- 25-WATT FLUORESCENT LAMP IS RATED FOR UP TO 14,000 HOURS.
- 50-WATT FLUORESCENT LAMP IS RATED FOR UP TO 20,000 HOURS.
- 110 & 210 SERIES LEDs ARE RATED FOR UP TO 50,000 HOURS.
- EXTRA DURABLE THICK-WALLED POLYCARBONATE OUTER TUBE PROTECTS THE LAMP.
- SOFT END CAPS PROVIDE IMPACT PROTECTION.
- BOOTED NEMA 5-15P PLUG AND RECEPTACLE PROVIDE MOISTURE TIGHT FIXTURE.
- INLINE ON-OFF SWITCH TURNS LIGHT ON AND OFF WITHOUT AFFECTING LIGHTS DOWNSTREAM.



**LED 110 Series  
Model No. 2020-5003**

## LED MODELS

Model No. Std. Tube	Description	Lumen Output	Fixture Length	Input Cord Length	Output Cord Length	Cord Specs	Case Qty.	Case Weight
2020-5003	110 Series, w Switch	2,400	51"	6'	1'	16 Ga. SJTOW	4	38 lbs.
2020-5007	210 Series, w Switch	2,400	27"	6'	1'	16 Ga. SJTOW	4	27 lbs.

## FLUORESCENT MODELS

Model No. Std. Tube	Description	Lumen Output	Fixture Length	Input Cord Length	Output Cord Length	Cord Specs	Case Qty.	Case Weight
1625-5025	25 Watt, w Switch	2,125	49"	6'	1'	16 Ga. SJTOW	4	28 lbs.
1650-5026	50 Watt, EMI Shielded, w Switch	3,750	34.5"	6'	1'	16 Ga. SJTOW	4	32 lbs.
1650-5061	50 Watt, less Switch	3,750	34.5"	6'	1'	16 Ga. SJTOW	4	27 lbs.
1650-5068	50 Watt, w Switch	3,750	34.5"	6'	1'	16 Ga. SJTOW	4	28 lbs.
1654-5000	Twin 54 Watt, w Switch	10,000	62"	6'	1'	16 Ga. SJTOW	4	32 lbs.

EVER HAD A STONE CHIP IN YOUR WINDSHIELD? A TECHNICIAN USING RESIN AND A CURING LIGHT CAN REPAIR INSTEAD OF REPLACE A WINDSHIELD. AS WITH ALL TOOLS, PICKING THE RIGHT CURING LIGHT CAN MAKE A TECHNICIAN MORE PRODUCTIVE. WHETHER YOU CHOOSE A 12VDC OR 120VAC GLOZONE™ CURING LIGHT, IN LESS THAN ONE MINUTE, RESIN CAN BE CURED, AND THE WINDSHIELD REPAIR COMPLETED! CURING LIGHTS CAN ALSO BE USED IN INDUSTRIAL APPLICATIONS INCLUDING CURING RESIN PATCHES THAT ARE USED TO REPAIR PLUMBING.

### Features

- 25-WATT LAMP DELIVERS 2125 LUMENS OF BRIGHT 5000K COLORED LIGHT.
- LAMP IS RATED FOR UP TO 10,000 HOURS AND IS VERY COOL OPERATING.
- DURABLE POLYCARBONATE OUTER TUBE PROTECTS THE LAMP.
- SOFT END CAPS PROVIDE IMPACT PROTECTION.
- BOOTED NEMA 5-15P PLUG AND RECEPTACLE PROVIDE MOISTURE TIGHT FIXTURE.
- UNIT IS AN INSTANT START, PLUG IN TO POWER TO TURN LIGHT ON, UNPLUG TO TURN LIGHT OFF.
- CLAMP KIT KEEPS MOISTURE AND DUST OUT OF THE LIGHT FIXTURE.
- HORIZONTAL HANGING HOOKS ARE INCLUDED.

### GLOZONE™ CURING LIGHTS



Model No. 1309-2002

Model No.	Description	Voltage	Switch Y/N	Cord Length	Cord Specs.	Case Qty.	Case Weight
1309-2002	26 LED GloZone™ Light	12VDC	Yes	20'	18/2 SJTOW	12	30 lbs.
1309-2504	26 LED GloZone™ Light	120VAC	Yes	25'	18/2 SJTOW	12	36 lbs.
1315-2002	15-Watt Fluorescent Light	12VDC	Yes	20'	18/2 SJTOW	12	40 lbs.
1315-2502	15-Watt Fluorescent Light	120VAC	Yes	25'	18/2 SJTOW	12	46 lbs.

HAVING TROUBLE FINDING THOSE PESKY LEAKS IN DIFFICULT, TIGHT LOCATIONS? THE 26 LED GLOZONE™ LEAK DETECTION LIGHTS DELIVER HIGH UV OUTPUT INTO TIGHT LOCATIONS, EVEN AT A 90-DEGREE ANGLE TO THE FIXTURE. FLASHLIGHTS MODELS CANNOT DELIVER UV OUT THE SIDE LIKE THE GLOZONE™ LIGHT!

### Features

- SLIM PROFILE GETS LIGHT INTO TIGHT SPOTS.
- LEDs ARE EXCEPTIONALLY COOL OPERATING.
- LEDs ARE RATED AT 50,000 HOURS.
- LED LAMP ASSEMBLY IS REPLACEABLE, AND MODELS ARE AVAILABLE WITH WHITE LAMP ASSEMBLY TO USE DURING THE REPAIR.

### GLOZONE™ LEAK DETECTION LIGHTS

Model No. 1920-7003

Model No.	Description	Voltage	Switch Y/N	Cord Length	Cord Specs.	Case Qty.	Case Weight
1920-7000	26 LED Leak Detection	12VDC	Yes	20'	18/2 SVT	6	12 lbs.
1920-7001	26 LED Leak Detection*	12VDC	Yes	20'	18/2 SVT	6	12 lbs.
1920-7003	26 LED Leak Detection	120VAC	Yes	20'	18/2 SVT	6	12 lbs.
1920-7004	26 LED White Light/Leak Detection	120VAC	Yes	20'	18/2 SVT	6	12 lbs.



\*NOTE: BATTERY CLAMP MODEL.



**BUILT WITH PRIDE  
IN THE U.S.A.**

WHETHER YOU NEED TO HANG YOUR LIGHT VERTICALLY OR HORIZONTALLY, THERE IS A SAF-T-LITE MOUNTING OPTION TO MEET YOUR NEEDS. RANGING FROM ADJUSTABLE HANGING STRAPS TO MAGNETIC MOUNTS TO PERMANENT DIRECT MOUNT, YOU CAN HANG YOUR SAF-T-LITE ON A MACHINE, ABOVE A WORKSTATION, IN A MOBILE SHELTER, OR AT A TEMPORARY WORK SITE. EACH MOUNTING OPTION GIVES YOU MAXIMUM VERSATILITY IN POSITIONING YOUR LIGHT EXACTLY WHERE YOU NEED IT.

**MOUNTING OPTIONS - LARGE DIAMETER LIGHTS**

**HANGING OPTIONS  
LARGE DIAMETER  
LIGHTS**

Model No.	Description	How Used
<i>JS</i> 5000-1051	Direct Mount Bracket	Bolt Directly to Work Surface
<i>JS</i> 5000-1077	Magnetic Mount	80lbs Magnet Attaches to Work Surface
<i>JS</i> 5000-1062	Machine Bracket Mount	Bolt Through Side or Bottom to Work Surface
5000-1055	Vertical Hook	Single Hook Hangs Light Vertically
5000-1296	Horizontal Hooks (set of 2)	Set of Two Hangs Light Horizontally
<i>JS</i> 5000-0862	48" Adjustable Hanging Kit	Set of Two Hangs Light Horizontally
5000-1360	24" Velcro Hanging Strap Kit	Set of Two Hangs Light Horizontally
5000-1149	Snap-Strap Hanging Kit	Set of Two Hangs Light Horizontally



**Model No. 5000-1051**



**Model No. 5000-1077**



**Model No. 5000-1062**



**Model No. 5000-1055**



**Model No. 5000-1296**



**Model No. 5000-0862**



**Model No. 5000-1360**



**Model No. 5000-1149**

WHAT DO YOU DO WHEN YOU HAVE A GREAT WORK LIGHT, BUT THE HOOK JUST DOESN'T QUITE HANG THE LIGHT WHERE YOU WANT IT? YOU TAKE A LOOK AT THE HANGING OPTIONS BELOW! WHETHER YOU WANT TO MAGNETICALLY HANG YOUR SAF-T-LITE, HANG IT BY ADJUSTABLE STRAPS, OR CLAMP THE LIGHT IN PLACE, WE HAVE AN OPTION FOR YOU. OUR LITE GRIP MODELS AT THE BOTTOM OF THE PAGE GIVE YOU A FLEXIBLE NECK THAT HOLDS THE LIGHT EXACTLY WHERE YOU WANT IT. IF THE 6" FLEXIBLE NECK IS NOT LONG ENOUGH, YOU CAN PURCHASE AN EXTENSION TO MAKE THE FLEX NECK 12 INCHES LONG!

## HANGING OPTIONS SMALL DIAMETER LIGHTS

### MAGMOUNTS™

Model No.	Description	Case Qty.	Case Wt.
5000-1030	Magmount, Style B	20	5 lbs.
5000-0000	SnapHook (Plastic Only)	20	2 lbs.
5000-0001	Magnahook (Magnet & Plastic Hook)	20	5 lbs.
5000-0003	Magmount Style A	20	5 lbs.
5000-0005	Magmount, Cord	20	4 lbs.



Model No. 5000-1030



Model No. 5000-0000

Model No. 5000-0001



Model No. 5000-0003



Model No. 5000-0005



### ADJUSTABLE HANGLING STRAPS

Model No.	Description	How Used
5000-0851	Adjustable Hanging Strap Kit	Hangs any Small Diameter Light Horizontally



Model No. 5000-0851



Model No. 1060-0004



Model No. 1060-4034

Model No. 1060-7044



Model No. 1060-8044

### LIGHT GRIPS™

Model No.	Description	Fits onto X dia. Fixture
1060-0004	3/4" x 6" flex neck	N/A
1060-4034	L Grip, 3/4 x 6" flex, 80# magnet	1 3/8" - 1 7/8"
1060-7034	L Grip, 3/4 x 6" flex, 2" clamp	1 3/8" - 1 7/8"
1060-7044	M Grip, 3/4 x 6" flex, 2" Clamp	1 5/8" - 2"
1060-8044	M Grip, 3/4" x 6" flex, machine bracket	1 5/8" - 2"

USE M GRIP WITH ALL STUBBY, STUBBY II, 15 WATT AND 25 WATT COMPACT MODELS.



**BUILT WITH PRIDE  
IN THE U.S.A.**

WHETHER YOU WANT TO CONVERT AN INCANDESCENT TROUBLE LIGHT OR REPLACE A DAMAGED LIGHT FIXTURE ON YOUR CURRENT REEL, SAF-T-LITE HEAD KITS ARE AN ECONOMICAL CHOICE. THE STUBBY AND STUBBY II FLUORESCENT MODELS BOTH COME WITH A ROUGH SERVICE BULB THAT WAS AWARDED A PATENT! THE 15-WATT SAF-T-LITE SPREADS LIGHT OVER A LARGER AREA. FOR THE LATEST IN TECHNOLOGY, THE STUBBY II, THE EDGE, AND STUBBY MODELS ARE ALL EXTRA DURABLE LED VERSIONS. WHICHEVER CHOICE YOU MAKE, YOU WILL HAVE A QUALITY LIGHT FIXTURE THAT IS BUILT IN THE USA!

**HEAD KITS**

**STUBBY II® LED**

Model No.	Description	Cord Install On
5165-0201	Stubby II LED, with Switch	18/2 and 18/3 SVT
5165-0202	Stubby II LED, with Switch	18/2, 18/3 and 16/2 SJTOW
5165-0203	Stubby II LED, with Switch	16/3 SJTOW

**THE EDGE™**

Model No.	Description	Cord Install On
5165-9884	The Edge LED, with Switch	16/3 SJTOW
5165-9886	The Edge LED, with Switch	18/2 and 18/3 SVT
5165-9888	The Edge LED, with Switch	18/2, 18/3 and 16/2 SJTOW

**STUBBY® LED**

Model No.	Description	Cord Install On
5165-0223	Stubby LED, with Switch	18/2, 18/3 and 16/2 SJTOW
5165-0224	Stubby LED, no Switch	18/2, 18/3 and 16/2 SJTOW
5165-0225	Stubby LED, with Switch	16/3 SJTOW
5165-0226	Stubby, with Switch	18/2 and 18/3 SVT

**STUBBY®**

Model No.	Description	Ballast	Cord Install On
5165-9501	Stubby, with Switch	Not Included	18/2, 18/3 and 16/2 SJTOW
5165-9504	Stubby, no Switch	Not Included	18/2, 18/3 and 16/2 SJTOW
5165-9512	Stubby, with Switch	Not Included	18/2 and 18/3 SVT
5165-9514	Stubby, with Switch	Not Included	16/3 SJTOW

**STUBBY II®**

Model No.	Description	Ballast	Cord Install On
5165-9519	Stubby II, with Switch	Included	16/3 SJTOW
5165-9520	Stubby II, with Switch	Included	18/2, 18/3 and 16/2 SJTOW
5165-9529	Stubby II, with Switch	Not Included	18/2, 18/3 and 16/2 SJTOW
5165-9541	Stubby II, No Switch	Not Included	18/2, 18/3 and 16/2 SJTOW
5165-9569	Stubby II, with Switch	Not included	18/2 and 18/3 SVT
5165-9590	Stubby II, with Switch	Included	18/2 and 18/3 SVT

**15-WATT SAF-T-LITE®**

Model No.	Description	Ballast	Cord Install On
5165-9502	15-Watt, with Switch	Not Included	16/2, 18/3 and 16/2 SJTOW



**Model No. 5165-0202**



**Model No. 5165-9888**



**Model No. 5165-0223**



**Model No. 5165-9501**



**Model No. 5165-9519**



**Model No. 5165-9502**

Also Available from General Manufacturing

# SAF/LITE™

**SERIES 5500 REEL  
w SAF-T-LOK OUTLET  
Up to 70' of Cord**



**40' MIDSIZE REEL  
TRIPLE OUTLET  
Portable or Permanent**



**SERIES 4000 REEL  
w DUPLEX OUTLET  
Available with Saf-T-Lok™**



**30' COMMERCIAL REEL  
w TRIPLE OUTLETS  
White Reel for Retail**



**General Manufacturing, Inc.  
1336 W Wiley Avenue  
Bluffton, IN 46714  
Phone: 260.824.3440  
sales@safllite.com  
www.safllite.com**